



特性: Specifications:

電器: Electrical:
 接觸阻抗: Contact Resistance: 30 milliohms MAX.
 耐電壓: Dielectric Withstanding Voltage: 500 V AC. AT Sea Level.
 絕緣阻抗: Insulation Resistance: 1000 MEGA ohms MIN.

機構: Mechanical:
 結合力: Mating Force: 4.0 KG MAX. 最大4kg.
 拔出力: Unmating Force: 0.7 KG MIN. 最少0.7kg.

材料: Material:
 塑膠: Housing: High Temperature Thermoplastics, UL 94V-0 耐高溫塑膠.

端子: Contact: Copper Alloy. 銅合金.
 鐵殼: Shell: Copper Alloy. 銅合金.

電鍍: Finish:
 端子: Contact: Plated Gold in Mating Area; Tin/Lead On Solder Tails. 接觸點鍍金, 腳鍍錫鉛.

鐵殼: Shell: Tin/Lead Plating. 鍍錫鉛

玄茂科技股份有限公司
HSUAN MAO TECHNOLOGY CO., LTD.

UNIT

SCALE

PART NAME

MM

2:1

IEEE 1394- 4Pin Female
 Right Angle /Black Insulator

APPD.

CKD.

TOLERANCE

PART NO.

REV.

制表日: 2002/12/04

DRAWING.

APPROVED

± 0.5

C8318-04FHBSB0

A

Jane