

CoolSplice | CoolSplice Connectors

TE Internal #: 2213600-8

Splices, 16 – 18 AWG Wire Size, 1.5 – .75 mm² Wire Size, Sealable, Splice Capacity 2, End Feed, Phosphor Bronze, Butt Splice Splice

View on TE.com >



Terminals & Splices > Splices > CoolSplice Quick Connect Splice











Wire Size: 1.5 – .75 mm²

Sealable: Yes

Splice Capacity: 2

Splice Features: End Feed

All CoolSplice Quick Connect Splice (12)

Features

Product Type Features

Sealable	Yes
Splice Type	Butt Splice
Serrated	No
Compatible With Discrete Wire Type	Solid, Stranded
Wire Insulation Support Retention Type	Insulation Support

Configuration Features

Splice Capacity	2
Compatible With Wire & Cable Type	Discrete Wire

Electrical Characteristics

Operating Voltage	400 VDC, 600 VAC
Current Rating	15 A

Body Features

Button Color	Red
Splice Features	End Feed



Primary Product Material	Phosphor Bronze
Mechanical Attachment	
Wire Insulation Support	With
Dimensions	
Wire Size	1.5 – .75 mm ²
Accepts Wire Insulation Diameter Range	3.5 mm[.138 in]
Overall Product Length	48 mm[1.89 in]
Usage Conditions	
UV Exposure Rated	F1
Insulation Option	Fully Insulated
Operating Temperature Range	-40 - 105 °C[-40 - 221 °F]
Operation/Application	
Heavy Duty	No
Compatible With Wire Base Material	Copper
Industry Standards	
Agency/Standard	IEC, UL
UL Flammability Rating	UL 94V-0, UL 94V-2
Agency/Standard Number	IEC 60988-2-3, UL 486C
Government Qualified Splice	No
Packaging Features	
Packaging Method	Box

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2022 (223) Candidate List Declared Against: JAN 2022 (223) Does not contain REACH SVHC
Halogen Content	BFR/CFR/PVC Free, but Br/Cl >900 ppm in other sources.



Solder Process Capability

Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts







Also in the Series | CoolSplice Connectors



Customers Also Bought







Documents



Product Drawings

COOLSPLICE LW 16/18 TO 16/18 AWG, SEAL

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2213600-8_C2.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2213600-8_C2.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2213600-8_C2.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

CoolSplice Large Wire flyer (Chinese)

CoolSplice Large Wire

CoolSplice Large Wire

English

Product Specifications

Application Specification

English

Product Environmental Compliance

Product Compliance

English

Product Compliance

English

Splices, 16 – 18 AWG Wire Size, 1.5 – .75 mm² Wire Size, Sealable, Splice Capacity 2, End Feed, Phosphor Bronze, Butt Splice Splice



Instruction Sheets

Instruction Sheet (U.S.)

English

Agency Approvals

VDE Certificate

English