

CA-T2T2-7.5M-22/3-R-BBG**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com



The right charging cable for every vehicle type
Simple, safe and quick

General ordering data

| | |
|------------|--|
| Version | AC charging cable, Plug type - charging point: Type 2, Plug type - vehicle side: Type 2, Charging power, max.: 22 kW, Number of phases: 3, Rated current: 32 A, Cable length: 7.5 m, Cable type: regular |
| Order No. | 2791300000 |
| Type | CA-T2T2-7.5M-22/3-R-BBG |
| GTIN (EAN) | 4064675070771 |
| Qty. | 1 pc(s). |

Creation date April 21, 2021 3:30:32 PM CEST

CA-T2T2-7.5M-22/3-R-BBG

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

| | |
|------------|---------|
| Net weight | 4,580 g |
|------------|---------|

Temperatures

| | | | |
|-----------------------|----------------|---------------------------------|-----------------------|
| Storage temperature | -40 °C...70 °C | Humidity at storage temperature | 5 - 95% rel. humidity |
| Operating temperature | -30 °C...55 °C | | |

Cable

| | | | |
|--------------|---------|--------------|-------|
| Cable colour | black | Cable length | 7.5 m |
| Cable type | regular | | |

Plug type

| | | | |
|----------------------------|------------------|--------------------------|--------|
| Plug type - charging point | Type 2 | Plug type - vehicle side | Type 2 |
| Plug colour | black, dark grey | | |

System requirements

| | | | |
|----------------------------------|---|--------------------|--------|
| Charging power, max. | 22 kW | Rated voltage (AC) | 480 V |
| Rated current | 32 A | Number of phases | 3 |
| Type of communication to vehicle | Control Pilot (CP), Proximity Pilot / Plug Present (PP) | Charging mode | Mode 3 |
| Protection degree | IP54 | | |

Approvals and norms

| | |
|-----------|---------------------------------------|
| Approvals | IEC 62196-1, IEC 62196-2, EN 50620 |
|-----------|---------------------------------------|

Material data

| | | | |
|---------------------------------------|--------|-----------------------------|-------|
| Max. relative humidity during storage | 95 % | Operating temperature, max. | 55 °C |
| Operating temperature, min. | -30 °C | Storage temperature, max. | 70 °C |
| Storage temperature, min. | -40 °C | | |

Classifications

| | | | |
|-------------|-------------|-------------|-------------|
| ETIM 6.0 | EC002897 | ETIM 7.0 | EC002897 |
| ECLASS 9.0 | 27-14-47-05 | ECLASS 9.1 | 27-14-47-05 |
| ECLASS 10.0 | 27-14-47-05 | ECLASS 11.0 | 27-14-47-05 |

Downloads

| | |
|--------------------|--|
| User Documentation | Safety notes |
| Brochure/Catalogue | Catalogues in PDF-format |