

# Wiha SoftFinish®.

The convenient expert for dry applications.



product  
design  
award

1997



*The right tool at a glance, thanks to the printed screw symbol on the handle end.*

The Wiha SoftFinish® zone features a solid moulded core with soft outer grip. This requires less force, yet achieves 40% more torque than conventional handles. The handle is shaped to fit comfortably in the hand, providing maximum through forces in dry working conditions.

If a stuck screw has to be loosened, a precise hammer blow can be applied to the solid steel cap. Due to the hex blade extending through the handle to the steel cap, there is no loss of impact energy.



*The solid steel cap at the end of the SoftFinish® handle enables controlled hammer blows, for example, when loosening a tight screw.*



*Due to the solid steel cap and hex blade extending through the handle, there is no loss of impact energy when a precise hammer blow is applied.*

*Blade with hex bolster for wrenches to use on particularly tight screws.*



## Wiha SoftFinish®.

- Multi-component SoftFinish® handle provides maximum user comfort
- Ergonomically perfect handle design
- Printed screw symbol on handle end for fast identification
- Available in versions with round blade, hex blade or hex blade with solid steel cap
- Blade made of high quality CVM-steel, through-hardened and chrome plated
- Wiha ChromTop®-finish on tip for a perfect fit every time

# Wiha SoftFinish®.

The convenient expert for dry applications.

## For hex nuts.



### 341 SoftFinish® hex nut driver.

#### Round blade.

Blade: Chrome-vanadium steel, through hardened, chrome-plated.  
Deep drawn socket.

Handle: Ergonomic Wiha SoftFinish® multi-component handle with roll-off protection.

Standards: DIN 3125.

Application: Particularly suitable for dry applications.

Order-No.	Ø	↔	↔	↕	⊥	↔
01018	4	125	236	30	6.9	10
01020	5	125	236	30	7.9	10
01021	5.5	125	236	30	7.9	10
01022	6	125	236	30	8.9	10
01023	7	125	243	36	10.9	10
01024	8	125	243	36	11.9	10
01025	9	125	243	36	12.9	10
01026	10	125	243	36	14.4	10
01027	11	125	249	41	15.9	5
01028	12	125	249	41	16.9	5
01029	13	125	249	41	18.4	5
01030	14	125	249	41	19.4	5
01031	15	125	249	41	21.9	5
01032	16	125	249	41	21.9	5
01033	17	125	249	41	23.4	5



### 347 SoftFinish® hex nut driver.

#### Round blade with hex bolster.

Blade: Chrome-vanadium steel, through hardened, chrome-plated.  
Deep drawn socket.

Handle: Ergonomic Wiha SoftFinish® multi-component handle with roll-off protection.

Standards: DIN 3125.

Application: Particularly suitable for dry applications.

Order-No.	Ø	↔	⊙	↔	↕	⊥	↔
01092	7	125	10	238	36	11.0	10
01093	8	125	10	238	36	12.0	10
01094	9	125	10	238	36	13.0	10
01095	10	125	10	238	36	14.5	10
01096	11	125	13	246	41	16.0	5
01097	12	125	13	246	41	17.0	5
01098	13	125	13	246	41	19.0	5

### 347 Zoll SoftFinish® hex nut driver. Inch sizes.

#### Round blade with hex bolster.

Blade: Chrome-vanadium steel, through hardened, nickel-plated.  
Deep drawn socket.

Handle: Ergonomic Wiha SoftFinish® multi-component handle with roll-off protection.

Application: Particularly suitable for dry applications.

Order-No.	Ø	↔	⊙	↔	↕	mm	⊥	↔
02836	3/16	125	10	231	30	4.76	8	10
02837	1/4	125	10	238	36	6.35	10	10
02838	5/16	125	10	238	36	7.94	12	10
02839	3/8	125	10	238	36	9.53	14	10
02840	7/16	125	13	246	41	11.11	16	10
02841	1/2	125	13	246	41	12.70	19	10

## For hex and triangular nuts.



### 343 SoftFinish® hex nut driver.

#### Short round blade.

Blade: Chrome-vanadium steel, through hardened, chrome-plated.  
Deep drawn socket.

Handle: Ergonomic Wiha SoftFinish® multi-component handle with roll-off protection.

Application: For working in confined spaces.

Order-No.	Ø	↔	↔	↕	⊥	↔
01076	5.5	65	176	30	8	10
01077	6	65	176	30	9	10
01078	7	65	183	36	11	10
01079	8	65	183	36	12	10
01081	10	65	183	36	14	10



### 372 SoftFinish® hex nut driver.

#### Flexible shaft for hard to reach areas.

Handle: Ergonomic Wiha SoftFinish® multi-component handle with roll-off protection.

Application: E.g. for tightening and loosening adjustable hose clamps.

Order-No.	Ø	↔	↔	↕	⊥	↔
01435	5	150	261	30	8	10
01436	5.5	150	261	30	8	10
01437	6	150	261	30	9	10
01438	7	150	268	36	11	10
01439	8	150	268	36	12	10
01440	10	175	293	41	14	10
01443	13	175	293	41	19	5



### 344 SoftFinish® triangular nut driver.

#### Round blade.

Blade: Chrome-vanadium steel, through hardened, chrome-plated.

Handle: Ergonomic Wiha SoftFinish® multi-component handle with roll-off protection.

Standards: DIN 22416.

Application: For triangular screws DIN 22424 and triangular nuts DIN 22425.

Order-No.	Ø	↔	↔	↕	⊥	↔	
26212	M4	125	6.8	236	30	11	10
26213	M5	125	8.3	236	30	13	10
26216	M6	125	10.05	236	30	16	10
26214	M8	125	12.05	243	36	18	10
26217	M10	125	15.05	243	36	22	10
26218	M12	125	16.55	249	41	24	10