Product data sheet Characteristics

ZB4BK1353

Harmony XB4, Illuminated selector switch head, metal, orange, Ø22, integral LED, 3 positions, stay put





Main

Range of product	Harmony XB4	
Product or component type	Head for illuminated selector switch	
Product compatibility	Integral LED	
Device short name	ZB4	
Bezel material	Chromium plated metal	
Head type	Standard	
Mounting diameter	22 Mm	
Sale per indivisible quantity	1	
Shape of signaling unit head	Round	
Type of operator	Stay put	
Operator profile	Orange standard handle	
Operator position information	3 positions +/- 45°	

Complementary

CAD overall width	29 Mm	
CAD overall height	29 Mm	
CAD overall depth	43 Mm	
Net weight	0.036 Kg	
Resistance to high pressure washer	7000000 Pa at 55 °C, distance : 0.1 m	
Mechanical durability	1000000 Cycles	
Electrical composition code	M3 for <4 contacts using single blocks in front mounting with integral LED M6 for <2 contacts using single blocks in front mounting with integral LED and-transformer M10 for <2 contacts using single blocks in front mounting with integral LED M4 for <4 contacts using single and double blocks in front mounting with integral LED	
Device presentation	Basic element	

Environment

TH 4070 °C 4070 °C Class I conforming to IEC 60536 IP66 conforming to IEC 60529 IP67 IP69 P69K NEMA 13 NEMA 4X K06 conforming to IEC 50102 JIS C8201-5-1 UL 508
4070 °C Class I conforming to IEC 60536 P66 conforming to IEC 60529 IP67 IP69 IP69K NEMA 13 NEMA 4X IK06 conforming to IEC 50102 JIS C8201-5-1
Class I conforming to IEC 60536 IP66 conforming to IEC 60529 IP67 IP69 IP69K NEMA 13 NEMA 4X IK06 conforming to IEC 50102 JIS C8201-5-1
P66 conforming to IEC 60529 IP67 IP69 IP69K NEMA 13 NEMA 4X IK06 conforming to IEC 50102 JIS C8201-5-1
IP67 IP69 IP69K NEMA 13 NEMA 4X IK06 conforming to IEC 50102 JIS C8201-5-1
NEMA 4X IK06 conforming to IEC 50102 JIS C8201-5-1
JIS C8201-5-1
EN/IEC 60947-5-1 EN/IEC 60947-5-4 EN/IEC 60947-1 EN/IEC 60947-5-5 CSA C22.2 No 14 JIS C8201-1
LROS (Lloyds register of shipping) DNV GL CSA UL listed BV
5 gn (f= 2500 Hz) conforming to IEC 60068-2-6
30 gn (duration = 18 ms) for half sine wave acceleration conforming- to IEC 60068-2-27 50 gn (duration = 11 ms) for half sine wave acceleration conforming- to IEC 60068-2-27

Packing Units

Package 3 Height	15 Cm	
Package 2 Length	40 Cm	
Package 2 width	30 Cm	
Package 2 Height	15 Cm	
Package 2 Weight	4.462 Kg	
Number of Units in Package 2	100	
Unit Type of Package 2	S02	
Package 1 Length	3.3 Cm	
Package 1 width	5.2 Cm	
Package 1 Height	5 Cm	
Package 1 Weight	42.0 G	
Number of Units in Package 1	1	
Unit Type of Package 1	PCE	
T doking office		_

Offer Sustainability

<u> </u>	
Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) [☑] EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	☑ China RoHS Declaration
Environmental Disclosure	Product Environmental Profile



Circularity Profile	End Of Life Information
California proposition 65	WARNING: This product can expose you to chemicals including: Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
Contractual warranty	
Warranty	18 months
Product Life Status :	Commercialised

