

ERSADUR long-life soldering tip series 102



■ All i-CON soldering stations with soldering irons i-TOOL, i-TOOL NANO, i-TOOL PICO

<p>0102CDLF200</p> <p>angled face, 20.0 mm</p>	<p>0102SDLF04</p> <p>pencil point, bent, 0.4 mm ø</p>	<p>0102SDLF06</p> <p>pencil point, bent, 0.6 mm</p>	<p>0102SDLF06L</p> <p>pencil point, bent, extended, 0.6 mm ø</p>
<p>0102SDLF08L</p> <p>pencil point, bent, extended, 0.8 mm ø</p>	<p>0102SDLF18</p> <p>chisel-shaped, bent, 1.8 mm ø</p>	<p>0102ADLF13</p> <p>angled face, 1.3 mm ø</p>	<p>0102ADLF15</p> <p>angled face, 1.5 mm ø</p>
<p>0102ADLF20</p> <p>angled face, 2.0 mm ø</p>	<p>0102ADLF40</p> <p>angled face, 4.0 mm ø</p>	<p>0102ZDLF100</p> <p>Wick-Tip, 10.0 mm</p>	<p>0102ZDLF150</p> <p>Wick-Tip, 15.0 mm</p>
<p>0102ZDLF200</p> <p>Wick-Tip, 20.0 mm</p>	<p>0102ZDLF370</p> <p>Wick-Tip, 37.0 mm</p>	<p>0102BDLF20</p> <p>PLCC blade</p>	<p>0102PDLF03</p> <p>soldering tip, lead-free, 0.3 mm</p>
<p>0102WDLF16</p> <p>PowerWell with concave portion, 1.6 mm ø</p>	<p>0102WDLF23</p> <p>PowerWell with concave portion, 2.3 mm ø</p>	<p>0102WDLF35</p> <p>PowerWell with concave portion, 3.5 mm ø</p>	<p>0102CDLF24A</p> <p>asymmetrical, 2.4 mm, 300µm Fe</p>
<p>0102CDLF46A</p> <p>asymmetrical, 4.6 mm, 300µm Fe</p>	<p>0102CDLF80A</p> <p>chisel-shaped, asymmetrical, 8.0 mm</p>		