



Transfer Multisort Elektronik Sp. z o.o.
 Ustronna 41 Str., 93-350 Lodz, Poland
 tel (+48) 42 645-54-44 | fax (+48) 42 645-54-70
www.tme.eu | export@tme.eu



Weller pb-free solder wire WSW SAC



Weller®

Manufacturer	WELLER
Type of solder	for soft soldering
Alloy composition	Sn96,5Ag3,0Cu0,5
Appearance	soldering wire
Flux content	3.5%
Package	reel
Melting point	217...221°C
Features	tip lifetime can be extended by up to 30%
Kind of solder	lead free

Symbol	Kind of flux	Diameter [mm]	Weight [g]
WEL.SAC-M1-03/010	halide, No Clean	0.3	100
WEL.SAC-M1-05/010	halide, No Clean	0.5	100
WEL.SAC-M1-08/025	halide, No Clean	0.8	250
WEL.SAC-M1-10/025	halide, No Clean	1	250
WEL.SAC-M1-05/05	halide, No Clean	0.5	500
WEL.SAC-M1-08/05	halide, No Clean	0.8	500
WEL.SAC-M1-10/05	halide, No Clean	1	500
WEL.SAC-M1-12/05	halide, No Clean	1.2	500
WEL.SAC-L0-08/025	halide-free	0.8	250
WEL.SAC-L0-10/025	halide-free	1	250
WEL.SAC-L0-03/010	halide-free	0.3	100
WEL.SAC-L0-05/010	halide-free	0.5	100
WEL.SAC-L0-05/05	halide-free	0.5	500
WEL.SAC-L0-08/05	halide-free	0.8	500
WEL.SAC-L0-10/05	halide-free	1	500

Product Information Management: www.parcet.eu

