

Polyamide-Fitting W


Metr., PG, NPT



Material	Polyamide
O-Ring	NBR
Protection Category	IP 54 with fixed conduit mounting IP 65
Operating Temperature	-20 °C – +80 °C (-4 °F – +176 °F)
Colours	black (RAL 9005)



// Protection against unintended disconnect. Use screwdriver to disassemble



AG	D mm	GL mm	H mm	L mm	mm	fits to Polyamide-Conduit DN	Number
M 16 x 1,5	20	8	23	43	19	10	1.513.1601.50
M 20 x 1,5	26,5	9	30,5	52	24	14	1.513.2001.50
M 25 x 1,5	38,5	11	40	70	33	23	1.513.2501.50
M 32 x 1,5	46	11	51,5	83	42	29	1.513.3201.50
PG 9	19	8	23	43	19	10	1.513.0901.14
PG 11	23	8	27	48	22	12	1.513.1101.14
PG 13,5	26,5	9	30,5	52	24	14	1.513.1301.14
PG 16	30	10	32,5	56	27	17	1.513.1601.14
PG 21	38,5	11	40	70	33	23	1.513.2101.14
PG 29	46	11	51,5	83	42	29	1.513.2901.14
NPT 3/8"	19	15	23	43	19	10	1.513.3801.70
NPT 1/2"	30	13	32,5	56	27	17	1.513.1217.70
NPT 3/4"	38,5	13	40	70	33	23	1.513.3401.70
NPT 1"	46	15	51,5	83	42	29	1.513.1001.70