

### Cirrus 80



Cirrus 80			
Nominal Power	at 10°C	300 / 600W	450 / 800W
Typical Max. In-Rush Current (A) RMS	at 230V AC	10	11
Typical Max. In-Rush Current (A) RMS	at 115V AC	15	14
Max. at Body Temperature	(°C)	55	80
Electrical Protection Class		I	I
Ingress Protection		IP20	IP20
Operating Temperature Range	(°C)	-40 to +60	-40 to +60
Fan Volumetric Flow	(m <sup>3</sup> /hr)	31 - 35	31 - 35
Fan Life Time - L10	at 40°C (hrs)	43.500	43.500
Nominal Input Voltage	(Depending on Variant)	115 / 230 V AC	115 / 230 V AC
Dimensions	Cross Section (mm)	82 x 110	82 x 110
Length	(mm)	150	150
Weight	(g)	785	785
Finger Guards at Inlet and Outlet		Yes	Yes

#### Ordering Example:

Type	Power	Heater Voltage	DIN clip	Filter
			1 / 0	1 / 0
C 80	600 W	230 V	1	1

Order Code Example: C 80 – 600 W – 230 V – 1 – 1

#### Features:

- High power to size ratio
- Light weight
- Easy to fit
- Screw terminals for easy wiring
- Dual power feature
- Independent fan circuit to aid climate cooling

#### Options:

- Filter Assembly\*
- Fixings - 35 mm DIN Rail clip (EN50022)

\* Typical power reduction of 10% when 30 PPI filter fixed.



DBK David+Baader GmbH

Industrial Heating

Nordring 26  
76761 Rülzheim

Phone: +49 (0) 7272 7704 - 0  
Fax: +49 (0) 7272 7704 - 1249

info@dbk-group.de  
www.dbk-group.de