

High Leverage Combination Pliers

DIN ISO 5746

02

35 % less effort required than with conventional combination pliers

With cutting edges (hardness approx. 63 HRC) for heavy duty

- > easier work due to optimised leverage
- > easier cutting, powerful gripping, bending and pulling
- > long cutting edges for thicker cables
- > with gripping zones for flat and round material, suitable for versatile use
- > High-grade special tool steel, forged, multi stage oil-hardened

02 02 225 T*

pliers with tether attachment point for mounting a fall protection



02 01 180



02 02 180



02 02 225 T



02 05 180



02 06 180



02 07 225



| Article No. | EAN 4003773- | ↔ mm | | Pliers | Head | Handles | Cutting capacities | | | | g |
|-------------|-----------------|---------|--|--------------------|----------|---|--------------------|------|------|-----------------|-----|
| | | | | | | | Ø mm | Ø mm | Ø mm | mm ² | |
| 02 01 180 | 033134 | 180 | | | | | 2.5 | 2.0 | 11.5 | 16 | 202 |
| 02 01 200 | 039679 | 200 | | black atramentized | polished | plastic coated | 2.8 | 2.2 | 13.0 | 25 | 298 |
| 02 01 225 | 013198 | 225 | | | | | 3.0 | 2.5 | 14.0 | 25 | 358 |
| 02 02 180 | 034896 | 180 | | | | | 2.5 | 2.0 | 11.5 | 16 | 240 |
| 02 02 200 | 034902 | 200 | | | | with multi-component grips | 2.8 | 2.2 | 13.0 | 25 | 342 |
| 02 02 225 | 043379 | 225 | | black atramentized | polished | | 3.0 | 2.5 | 14.0 | 25 | 409 |
| 02 02 225 T | 079934 | 225 | | | | with multi-component grips and integrated tether attachment point | 3.0 | 2.5 | 14.0 | 25 | 413 |
| 02 05 180 | 043072 | 180 | | | | | 2.5 | 2.0 | 11.5 | 16 | 238 |
| 02 05 200 | 043089 | 200 | | chrome plated | | with multi-component grips | 2.8 | 2.2 | 13.0 | 25 | 342 |
| 02 05 225 | 010005 | 225 | | | | | 3.0 | 2.5 | 14.0 | 25 | 400 |
| 02 06 180 | 010012 | 180 | | | | | 2.5 | 2.0 | 11.5 | 16 | 247 |
| 02 06 200 | 010029 | 200 | | chrome plated | | insulate with multi-component grips, VDE-tested | 2.8 | 2.2 | 13.0 | 25 | 343 |
| 02 06 225 | 010036 | 225 | | | | | 3.0 | 2.5 | 14.0 | 25 | 401 |
| 02 07 200 | 022299 | 200 | | chrome plated | | with dipped insulation, VDE-tested | 2.8 | 2.2 | 13.0 | 25 | 380 |
| 02 07 225 | 022305 | 225 | | | | | 3.0 | 2.5 | 14.0 | 25 | 486 |

* Other tools with tethering can be found from page 254 ff