



APart

**APart PM7400MKII
PRE-AMPLIFIER**



The PM7400MKII is a very easy to operate stereo pre-amplifier that is suitable for many applications like clubs, bars, restaurants, fitness, audiovisual, ...

The pre-amplifier is equipped with 6 line inputs and 2 microphone inputs (phantom power via internal switch). The microphone can be plugged-in via the balanced jack on the front or via the balanced XLR inputs at the back of the amplifier.

A separate volume and tone control is available for the microphone and line inputs. Microphone input 1 has an adjustable voice activated mute (VOX) that mutes all other inputs. A contact mute at the back of the PM7400MKII mutes the music sources.

The pre-amplifier is equipped with 2 stereo outputs. The volume of each output can be controlled individually. Together with the fact that it will only take 1 unit of rackspace, its excellent sound quality will make the PM7400MKII part of your audio solution!

TECHNICAL SPECIFICATIONS

Input Line 1	XLR Balanced 0dB, 20 kOhm
Line 2-6	RCA Cinch, 500 mV, 10 kOhm
Mic 1-2	Front: Jack balanced -50 dB / 600 Ohm Rear: Combo balanced -50 dB / 600 Ohm
Output Zone 1	RCA Cinch 0dB / 100 Ohm
Zone 2	XLR Balanced 0 dB / 100 Ohm
Frequency Response	20 Hz to 25 kHz
Tone control MIC	3-band tone control
Tone control Line	3-band tone control
Mute contact	Via screw
Distortion	< 0.01%
Dimensions (H x W x D)	44 x 483 x 275 mm
Weight	3.1 Kg