

**FFKDSA1/H-5,08**

Order No.: 1791868

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1791868>

PC terminal block, Nominal current: 6 A, Nom. voltage: 63 V, Pitch: 2.54 mm, Number of positions: 1, Type of connection: Spring-cage connection, Assembly: Soldering, Conductor/PCB connection direction: 0 °, Color: green

Commercial data	
EAN	4017918044473
Pack	50 pcs.
Customs tariff	85369010
Weight/Piece	0.000873 KG
Catalog page information	Page 93 (CC-2007)

## Product notes

WEEE/RoHS-compliant since:  
01/01/2003

<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

## Certificates / Approvals



Certification

CCA, CSA, CUL, GOST, KEMA, UL

**CSA**

Nominal voltage $U_N$	150 V
Nominal current $I_N$	6 A
AWG/kcmil	20

**CUL**

Nominal voltage $U_N$	150 V
Nominal current $I_N$	6 A
AWG/kcmil	26-20

**UL**

Nominal voltage $U_N$	150 V
Nominal current $I_N$	6 A
AWG/kcmil	26-20

**Address**

PHOENIX CONTACT AB  
Linvägen 2  
S-14144 Huddinge, Sweden  
Phone +46/8/608-64-00  
Fax +46/8/608-64-99  
<http://www.phoenixcontact.se>



© 2009 Phoenix Contact  
Technical modifications reserved;