

UIB SERIES UNIVERSAL INTERFACE BREADBOARD



FEATURES

- With considerable system expansion available for the computer (Binding post and various optional connectors are available for end users to fit on connector socket).
- With EP-3 edge plate, it accepts big size electronic part with big size or without pin such as potentiometer, switch, light etc....
- 4 binding posts are equipped for external power supply input.
- Special suggested sturdy jump wire is optionally available for connecting pin of universal connector and breadboard.
- Specially suggested KS-350 jump wire kit is optional and suitable for layout of circuit.



ROUND HOLE

SPECIFICATION

MODEL	DIMENSION(m/m)			TIE-POINTS	5 INCONNECTED CLIP	25 INCONNECTED CLIP	BINDING POST	IC CAPACITY 14 PINS	BACK-PLATE	WEIGHT (gm)
	LENGTH	WIDTH	HEIGHT							
UIB-68	367	250	20	4640	768	32	4	54	PLASTIC STAND	1,300
UIB-46	370	200	20	3160	512	24	4	36	PLASTIC STAND	1,000
UIB-34	230	250	20	2320	384	16	4	27	PLASTIC STAND	800

UC-SERIES UNIVERSAL CONNECTOR SET

REF.NO.	ITEM	DESCRIPTION	*S/O
UC-01	CARD EDGE connector	62 contacts, 2.54 mm pitch	O
UC-02	D Sub connector	25 contacts, male & female	S
UC-03	STRAIGHT HEADER connector	60 contacts	O
UC-04	CARD EDGE connector	56 contacts, 3.96 mm pitch	O
UC-05-3	DIN 41612 connector	32 contacts, 5.08 mm pitch	O
UC-05-6	DIN 41612 connector	64 contacts, 2.54 mm pitch	O
UC-05-9	DIN 41612 connector	96 contacts, 2.54 mm pitch	O
UC-06	CENTRONIC connector	36 contacts	O

*S is standard , O is option