



## PRODUKTINFORMATION

Vi reserverar oss mot fel samt förbehåller oss rätten till ändringar utan föregående meddelande

### **ELFA artikelnr**

**54-126-22 Fläkt 60x60mm 12VDC JF0620B1L**

**54-126-30 Fläkt 60x60mm 12VDC JF0620B1H**

**54-126-48 Fläkt 60x60mm 24VDC JF0620B2H**

# DC FAN

JAMICON®

## 60X60X20 mm



### SPECIFICATIONS

Model	Bearing	Rated Voltage (V)	Operating (V)	Air Flow (CFM)	Static Pressure (mmH <sub>2</sub> O)	Speed (R.P.M)	Rated Current (Amp)	Input Power (Watt)	Noise (dBA)	Life Expectancy (Hour)	Weight (g)
JF0620B1L	B	12	10.2~13.8	12.90	3.48	3500	0.13	1.56	22.5	64000	50
JF0620S1L	S			12.90	3.48	3500	0.13	1.56	22.5	38000	
JF0620B1M	B			14.45	4.35	4000	0.15	1.80	26.8	56000	
JF0620S1M	S			14.45	4.35	4000	0.15	1.80	26.8	33000	
JF0620B1H	B			15.90	4.86	4500	0.17	2.04	30.4	50000	
JF0620S1H	S			15.90	4.86	4500	0.17	2.04	30.4	30000	
JF0620B2L	B	24	20.4~27.6	12.90	3.48	3500	0.09	2.16	22.5	64000	
JF0620S2L	S			12.90	3.48	3500	0.09	2.16	22.5	38000	
JF0620B2M	B			14.45	4.35	4000	0.11	2.64	26.8	56000	
JF0620S2M	S			14.45	4.35	4000	0.11	2.64	26.8	33000	
JF0620B2H	B			15.90	4.86	4500	0.13	3.12	30.4	50000	
JF0620S2H	S			15.90	4.86	4500	0.13	3.12	30.4	30000	

Specifications Subject to change without notice

- Frame: Plastic Material UL 94V-0
- Blade: Plastic Material UL 94V-0
- Insulation Resistance: 50M ohm min. at 500 VDC (between frame and terminal)
- Dielectric Strength: 5mA max. at 500 VAC 60 Hz one minute (between frame and terminal)
- Operating Temperature: -10°C to +70°C  
Option: -20°C to +80°C

