

DC FAN

JAMICON®

25X25X10 mm

- **Frame** : Plastic Material UL 94V-0
- **Impeller** : Plastic Material UL 94V-0
- **Speed Range** : ±15%



SPECIFICATIONS

Model	Bearing	Rated Voltage (V)	Operating Voltage (V)	Air Flow (CFM)	Static Pressure (mmH ₂ O)	Speed (R.P.M)	Rated Current (Amp)	Input Power (Watt)	Noise (dBA)	Weight (g)			
KF0210B5H	Two Ball	5	4.25~5.75	2.77	7.64	13000	0.20	1.0	31.8	7.0			
KF0210B5M				2.12	4.80	10000	0.16	0.8	25.2				
KF0210B5L				1.43	2.45	7000	0.10	0.5	20.5				
KF0210C5H	Ball + Sleeve			2.77	7.64	13000	0.20	1.0	31.8				
KF0210C5M				2.12	4.80	10000	0.16	0.8	25.2				
KF0210C5L				1.43	2.45	7000	0.10	0.5	20.5				
KF0210S5H	Sleeve			2.77	7.64	13000	0.22	1.1	31.8				
KF0210S5M				2.12	4.80	10000	0.20	1.0	25.2				
KF0210S5L				1.43	2.45	7000	0.14	0.7	20.5				
KF0210B1H	Two Ball			12	10.2~13.8	2.77	7.64	13000	0.13		1.6	31.8	7.0
KF0210B1M						2.12	4.80	10000	0.07		0.8	25.2	
KF0210B1L						1.43	2.45	7000	0.06		0.7	20.5	
KF0210C1H	Ball + Sleeve	2.77	7.64			13000	0.12	1.4	31.8				
KF0210C1M		2.12	4.80			10000	0.07	0.8	25.2				
KF0210C1L		1.43	2.45			7000	0.06	0.7	20.5				
KF0210S1H	Sleeve	2.77	7.64			13000	0.13	1.5	31.8				
KF0210S1M		2.12	4.80			10000	0.11	1.3	25.2				
KF0210S1L		1.43	2.45			7000	0.10	1.2	20.5				

Specifications subject to change without notice

