

DC FAN

JAMICON®

50X50X10 mm

KF0510-00 Series



- **Frame** : Plastic Material UL 94V-0
- **Impeller** : Plastic Material UL 94V-0
- **Speed Range** : $\pm 10\%$

SPECIFICATIONS

Model	Bearing	Rated Voltage (V)	Operating Voltage (V)	Air Flow (CFM)	Static Pressure (inchH ₂ O)	Speed (R.P.M.)	Input Current (Amp)	Input Power (Watt)	Nominal Power (Watt)	Noise (dBA)	Weight (g)
KF0510B5H-00	Dual Ball	5	4.25~5.75	10.56	0.112	5300	0.14	0.70	1.1	30.8	20
KF0510B5M-00				9.27	0.092	4500	0.12	0.60	0.9	26.6	
KF0510B5L-00				7.18	0.058	3500	0.08	0.40	0.6	21.9	
KF0510C5H-00	Ball + Sleeve			10.56	0.112	5300	0.14	0.70	1.1	30.8	
KF0510C5M-00				9.27	0.092	4500	0.12	0.60	0.9	26.6	
KF0510S5H-00				Sleeve	10.56	0.112	5300	0.22	1.10	1.1	
KF0510S5M-00	9.27	0.092	4500		0.15	0.75	1.1	26.6			
KF0510S5L-00	7.18	0.058	3500		0.12	0.60	0.7	21.9			
KF0510B1H-00	Dual Ball	12	10.2~13.8	10.56	0.112	5300	0.11	1.32	1.6	30.8	
KF0510B1M-00				9.27	0.092	4500	0.08	0.96	0.8	26.6	
KF0510B1L-00				7.18	0.058	3500	0.06	0.72	0.7	21.9	
KF0510C1H-00	Ball + Sleeve			10.56	0.112	5300	0.11	1.32	1.6	30.8	
KF0510C1M-00				9.27	0.092	4500	0.08	0.96	1	26.6	
KF0510S1H-00				Sleeve	10.56	0.112	5300	0.13	1.56	1.9	30.8
KF0510S1M-00	9.27	0.092	4500		0.08	0.96	1	26.6			
KF0510S1L-00	7.18	0.058	3500		0.07	0.84	0.8	21.9			

Specifications subject to change without notice

