

SKUB

TF Kable



Loudspeaker cables

Construction

Conductor: annealed copper, class 6 flexible
Insulation: special PVC compound type TI2
Colour of insulation: black, grey, white, red-black or according to request
Identification: 1 core smooth, 1 core corrugated

Temperature range: -30°C to +70°C

Flame propagation: IEC 60332-1-2

Minimum bending radius: 6 x smaller dimension of flat cable

The product is conformed with the RoHD Direktive 2002/95/CE

Standard length cable packing: 50 and 100 m in spools.
Other forms of packing and delivery are available on request.

SKUB

Number and cross-sectional area of conductor	Maximum diameter of wires in conductor	Approximate dimension	Approximate net weight of cables
mm ²	mm	mm	kg/km
2 x 0,5	0,16	2,1 x 4,5	16
2 x 0,75	0,16	2,3 x 4,9	22

TELE-FONIKA KABLE S.A. 30-663 Kraków, ul. Wielicka 114, POLAND

Head Office: 30-663 Kraków, ul. Wielicka 114
Export Department: 30-663 Kraków, ul. Wielicka 114
export@tfkable.pl
www.tfkable.pl

tel.: +48 12 652 50 00
tel.: +48 12 652 59 05

fax: +48 12 652 51 56
fax: +48 12 652 59 28