1-1534155-1 ACTIVE

AMP | MQS

TE Internal #: 1-1534155-1

MQS, Housing for Male Terminals, Wire-to-Wire, 2 Position, 2.54

mm Centerline, Black, Signal, -40 – 176 °F [-40 – 80 °C]

View on TE.com >



Connectors > Automotive Connectors > Connector Housings > MQS, CONNECTOR HOUSING



Connector & Housing Type: Housing for Male Terminals

Mating Tab Width: .63 mm [.025 in] Connector System: Wire-to-Wire

Number of Positions: 2 Centerline (Pitch): 2.54 mm

All MQS, CONNECTOR HOUSING (575)

Features

Product Type Features

Connector & Housing Type	Housing for Male Terminals
Connector System	Wire-to-Wire
Sealable	No
Hybrid Connector	No
Primary Locking Feature	On the Terminal
Configuration Features	
Number of Positions	2
Number of Rows	1
Electrical Characteristics	
Operating Voltage	12 VDC
Nominal Voltage Architecture	12 V

Body Features

Cable Exit Angle	180°
Body Material	PBT GF
Primary Product Color	Black

Contact Features

Mating Tab Width	.63 mm[.025 in]
S S S S S S S S S S S S S S S S S S S	



Mechanical Attachment	
Mounting Feature	Without
Terminal Position Assurance	Yes
Strain Relief	No
Mating Alignment Type	Polarized
Housing Features	
Centerline (Pitch)	2.54 mm
Dimensions	
Product Width	28.8 mm[1.134 in]
Product Height	11.2 mm[.441 in]
Usage Conditions	
Operating Temperature (Max)	70 °C, 75 °C, 80 °C[158 °F][167 °F][176 °F]
Operating Temperature Range	-40 - 80 °C[-40 - 176 °F]

Operation/Application

Circuit Application	Signal
Industry Standards	
UL Flammability Rating	UL 94HB

Packaging Features

Packaging Method	Package
Other	
Serviceable	Yes
Connector Position Assurance Capable	No

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2022 (223) Candidate List Declared Against: JAN 2022 (223) Does not contain REACH SVHC



Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per
	homogenous material. Also BFR/CFR/PVC
	Free

Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



TE Part # 1-1534113-1



TE Part # 1534112-1 MQS RETAINER FOR 2POS REC.HSG



TE Part # 1534027-1 MQS VERRIEGLUNG F2P





Also in the Series | MQS



Automotive Connector Caps & Covers (132)



Automotive Connector EMC Shielding (2)



Automotive Connector Locks & Position Assurance(29)



Automotive Housings(500)





Automotive Seals & Cavity Plugs(26)



Automotive Terminals(93)




Data Connectivity Headers(1)



Insertion & Extraction Tools(42)



Other Automotive Connector Accessories(13)



PCB Headers & Receptacles(206)

Customers Also Bought



MQS, CONNECTOR HOUSING



TE Part #1452601-1 2 POS. GET MALE-HSG.,ASSY



TE Part #1563123-1 10POS, MIXED,REC HSG



Documents

Product Drawings
2POS MQS TAB

English

CAD Files

Customer View Model

ENG_CVM_CVM_1-1534155-1_A.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1-1534155-1_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1-1534155-1_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

MQS, Housing for Male Terminals, Wire-to-Wire, 2 Position, 2.54 mm Centerline, Black, Signal, -40 – 176 °F [-40 – 80 °C]



Datasheets & Catalog Pages

Micro Quadlok Interconnection System (MQS)

English

Product Specifications

Application Specification

English

Product Environmental Compliance

Product Compliance

English

Product Compliance

English