



EMPTY ENCLOSURE

TG ABS 3023-9-to



TG ABS 3023-9-to

Empty enclosure

CUSTOMIZE

302 x 232 x 90 mm
Article number: 10101301

Empty enclosure, Base: ABS, light grey similar to RAL 7035, Cover: polycarbonate, transparent, with quick closing, with cover retainer



Technical data

Measures

| | |
|---------------|--------|
| Width: | 302 mm |
| Length: | 232 mm |
| Height: | 90 mm |
| Inner height: | 74 mm |

Material:

| | |
|--------------|-----------------------------------|
| Box: | ABS, grey similar RAL 7035 |
| Cover: | Polycarbonate, transparent |
| Sealing: | Polyurethane |
| Cover screw: | stainless steel V2A, fast-closing |
| material: | ABS |

Accessory

DAE M12 - Pressure balance element

LFR - Stepped drill

NS 35-283,5 - Standard rail

TG ABL - External fixing lugs kit

TG DVS-57 - Cover retainer

TG ISS - Interior hinge set

TG MPI-3023 - Mounting plate

TG MPS-3023 - Mounting plate

TG PST2 - Sealing kit

TS 15-283,5 - Standard rail



EMPTY ENCLOSURE

TG ABS 3023-9-to

Other attributes

| | |
|-------------------------------------|---|
| Ingress protection: | IP66/IP67 acc. EN 60529 / DIN VDE 0470-1 |
| Impact resistance: | IK07 acc. DIN EN 5012 / VDE 0470 Part 100 |
| Protection class: | II - isolate protection acc. VDE 0106 |
| Rated insulation voltage AC: | 690 V |
| Rated insulation voltage DC: | 1000 V |
| Heavy metals-free: | Yes |
| PVC-free: | Yes |
| Silicone-free: | Yes |
| Cable entries: | No |
| Combustion behaviour acc. to UL 94: | HB acc. UL94 |
| Combustion behaviour acc. to VDE: | 650°C acc. VDE 0471/ EN 60695 |
| weatherproof: | No |

Environmental attributes

| | |
|---|--------|
| Ambient temperature (min.): | -25 °C |
| Ambient temperature (max.): | 40 °C |
| Ambient temperature (24 h): | 35 °C |
| Max. rel. humidity at 25° C (short term): | 95% |
| Max. rel. humidity at 40° C: | 50% |