



EMPTY ENCLOSURE

TK PS 3625-16-tm

TK PS 3625-16-tm

Empty enclosure

CUSTOMIZE

361 x 254 x 165 mm
Article number: 10651201

Empty enclosure, Base: polystyrene, Grey, similar to RAL 7035, Cover: polycarbonate, transparent

with metric knockouts



Technical data

Measures

| | |
|---------------|--------|
| Width: | 361 mm |
| Length: | 254 mm |
| Height: | 165 mm |
| Inner height: | 150 mm |

Material:

| | |
|--------------|--|
| Box: | Polystyrene, light grey, similar to RAL 7035 |
| Cover: | Polycarbonate, transparent |
| Sealing: | Polyurethane |
| Cover screw: | Polyamide 6, fiber-glass reinforced |
| material: | polystyrene |

Accessory

- ASS-gro - External hinge set
- HBA - Mounting material
- NS 35-216 - Standard rail
- NS 35-336 - Standard rail
- TK ABL - External fixing lugs kit
- TK MPI-3625 - Mounting plate

Environmental attributes

| | |
|---|--------|
| Ambient temperature (min.): | -25 °C |
| Ambient temperature (max.): | 40 °C |
| Ambient temperature (24 h): | 35 °C |
| Max. rel. humidity at 25° C (short term): | 95% |
| Max. rel. humidity at 40° C: | 50% |



EMPTY ENCLOSURE

TK PS 3625-16-tm

Other attributes

| | |
|-------------------------------------|---|
| Ingress protection: | IP66 - acc. EN 60529 / DIN VDE 0470-1 |
| Impact resistance: | IK07 acc. DIN EN 5012 / VDE 0470 Part 100 |
| Protection class: | II - isolate protection acc. VDE 0106 |
| Rated insulation voltage AC: | 690 V |
| Rated insulation voltage DC: | 1000 V |
| Heavy metals-free: | Yes |
| PVC-free: | Yes |
| Silicone-free: | Yes |
| Fitted for outdoor application: | No |
| Combustion behaviour acc. to UL 94: | HB acc. UL94 |
| Combustion behaviour acc. to VDE: | 650°C acc. VDE 0471/ EN 60695 |
| sealable: | Yes |
| weatherproof: | No |
| Cable entries: | Yes |
| Cover screw torque: | 1.2 N m |
| Domed fastener torque: | 1.5 N m |
| External hinge torque: | 1.5 N m |