

Data Sheet FUJITSU Accessory Car Truck Power Adapter 90 Accessories

Charge your batteries everywhere and anytime

People who are often on business or private trips want to power up their handhelds, tablet PCs and notebooks anywhere and anytime. The Fujitsu Car/Truck Power Adapter 90 will charge your Tablet PC or notebook anywhere a 12 V or 24 V power supply is available. NEW: The Car/Truck Power Adapter 90 now charges 19V and 12V devices.

Reliability

- Guaranteed quality and stability
- Constant current regulation ensures stable charging of batteries
- Everything you need from one company

Mobility

- Through a wide input voltage range which ensures that the Car/Truck Power Adapter 90 can be used not only with cars but also in lorries, boats, planes anywhere where 12 V or 24 V power supplies are available
- Simply select the correct MCS Connector and use the charger for your handheld, Tablet PC or notebook
- USB charging port for mobile devices

Security

- The adapter comes with short circuit protection and under-voltage protection:
- The Car/Truck Power Adapter 90 will not enable charging if the voltage on the line is not within the specified limits
- Over voltage protection
- Over temperature protection



Car Truck Power Adapter 90

Imput characteristics Voltage range: 11 - 32VDC Input lase 12A (Ibs) Protection: Reverse polarisy, Under voltage protection, over temperature protection	d	
Input (use 12A (file) Protection. Reverse polarity, Under voltage protection, over temperature protection	Charger	
Protection: Reverse polarity, Under voltage protection, over temperature protection Convection cooled Operating temperature: -40°C to 40°C at max 2000m above sea level Non operating temperature: -40°C to 46°C at max. 15000m above sea level Non operating temperature: -40°C to 65°C at max. 15000m above sea level Non operating temperature: -40°C to 65°C at max. 15000m above sea level Non operating temperature: -40°C to 65°C at max. 15000m above sea level Non operating temperature: -40°C to 65°C at max. 15000m above sea level Non operating temperature: -40°C to 65°C at max. 15000m above sea level Non operating temperature: -40°C to 65°C at max. 15000m above sea level Non operating temperature: -40°C to 65°C at max. 15000m above sea level Non operating temperature: -40°C to 65°C at max. 15000m above sea level Non operating temperature: -40°C to 65°C at max. 15000m above sea level Non operating temperature: -40°C to 65°C at max. 15000m above sea level Non operating temperature: -40°C to 65°C at max. 15000m above sea level Non operating temperature: -40°C to 65°C at max. 15000m above sea level Non operating temperature: -40°C to 65°C at max. 15000m above sea level Non operating temperature: -40°C to 65°C at max. 15000m above sea level Non operating temperature: -40°C to 65°C at max. 15000m above sea level None of the sea of the	Input characteristics	
Convection cooled Operating temperature: 20°C to 40°C at max. 15000m above sea level Non operating temperature: 40°C to 8°C at max. 15000m above sea level Himmility: 5 to 95% r.H., non condensing Output characteristics Output: Voltoge range 10 - 240°C cominal / 85W max. Consant current, 6 Amax. (current protection. over voltage protection. Short circuit. over current protection. Output: USB:SVDC nominal / 1A max / 5W max Protection: Short circuit. over current protection. Efficiency, typical 96% at 100% load Connector and Cable Specification Input Connector: Ogarette lighter adapter with multiple connector system input cable length: 100cm Output cable length:		
Operating temperature - 20°C to 40°C at max 2000m above sea level Non operating temperature - 40°C to 45°C at max 15000m above sea level Humidity: 5 to 95% r.H., non condensing Output characteristics Output ! Voltge range 10 - 24VDC nominal / 85W max Constant current, 64 max (current limitation) Protection: Short circuit, over current protection, over voltage protection, over temperature protection Efficiency: typical 96% at 100% load Imput Connector Organite lighter adapter with multiple connector system Imput Connector Organite lighter adapter with multiple connector system Imput Connector Organite lighter adapter with multiple connector system Imput Connector Organite lighter adapter with multiple connector system Imput Connector		
Non operating temperature. 40°C to B5°C at max. 15000m above sea level Humidity. 5 to 95% r.H., non condensing Output characteristics Output: Voltge range 10 - 24VDC nominal / 85W max. Constant current, 64 max. (current limitation) Protection. Short circuit, over current protection, over voltage protection, over temperature protection Connector and Cable Specification Input Connector: 100cm limitation of 100cm limitati		
Humidity: 5 to 95% kH., non condensing		
Consant curent, 6A max. (curent limitation) Protection: Short circuit, ower curent protection, over voltage protection; Short circuit, ower curent protection Output USB:5VDC nominal / 1A max / 5W max Protection: Short circuit, ower current protection Efficiency: Spical 96% at 100% load Connector and Cable Specification Input Connector: Cigarette lighter adapter with multiple connector system Input cable length: 1000cm Output Connector: Typ C03 for 19V pin length: 14.2 + 0.5 mm; outer diameter: 5.5 mm Iyp C05 for 12V pin length: 9.6 +-0.3 mm; outer diameter: 3.4 mm Iyp C05 for 12V pin length: 10.0 - 0.4 mm; outer diameter: 3.0 mm Output 2: USB receptade, type A Color Black Device Classification Power consumption 85W + 5W (USB) Power supply input 11 - 32V DC Power supply output 12V and 19V Devise Classification Power supply output 12V and 19V Devise Classification Europe EUSA/Canada FCC Class B CUlus Australia/New Zealand Circk Compliance link Hits://sp.1s.fujtsu.com/sites/certificates Wiscellaneous Dimensions (W x D x H) Wiscellaneous Dimensions (W x D x H) Power supply on the supply control to the supply on the supply control to the supply		
Protection: Short circuit, over current protection, over voltage protection Dutput USB-SVDC nominal / 1A max / 5W max Protection Efficiency: typical 96% at 100% load Connector and Cable Specification Input Connector: Ogarette lighter adapter with multiple connector system Input Cable length: 100cm Output Cable length: 100cm Output Cable length: 100cm Pyp (03 for 19V pin length: 14, 2 + 0.5 mm; outer diameter: 3.5 mm yp (03 for 19V pin length: 9.6 + 0.3 mm; outer diameter: 3.4 mm yp (05 for 19V pin length: 10.0 + 0.4 mm; outer diameter: 3.0 mm output cable length: 100cm Output 2: USB receptacle, type A Color Black Device Classification Power supply output 11 - 32V DC Power supply output 12 V and 19V Devise Classification Europe EE USA/Canada CTick Compliance link https://sp.ts.fujitsu.com/sites/certificates Miscellaneous Dimensions (W x D x H) Miscellaneous Dimensions (W x D x H) Sea 391 - F2613-16.10 EAN: 4051554418304 Warranty period Warranty type Bing.In / Send-In Service (depending on country) Warranty Terms & Conditions https://sp.port.s.fujitsu.com/varranty Warranty Terms & Conditions https://sp.port.s.fujitsu.com/varranty Warranty Terms & Conditions http://sp.port.s.fujitsu.com/varranty	Output characteristics	
Dutput USB:SVDC nominal /1A max / 5W max Protection Connector and Cable Specification Input Connector: Usp and East 100% load 100% loa		
Protection: Short circuit, over current protection Efficiency: typical 96% at 100% load Connector and Cable Specification Input Connector: Ggarette lighter adapter with multiple connector system Input cable length: 100cm Upput 2003 for 19V pin length: 14.2 + 0.5 mm; outer diameter: 5.5 mm Iyp C06 for 12V pin length: 10.0 + 0.4 mm; outer diameter: 3.0 mm Output cable length: 100cm Output 2: USB receptacle, type A Color Black Device Classification Power consumption 85W + SW (USB) Power supply input 11 - 32V DC Power supply output 12V and 19V Devise Classification Europe CE USA/Canada FCC Class B CULus Australia/New Zealand C-Tick Compliance link https://sp.ts.fujitsu.com/sites/certificates Miscellaneous Miscellaneous Dimensions (W x D x H) 11 5 x 53.7 x 21.5 mm Weight 250g w/o cables and connectors Order code Warranty period 2 years (depending on country) Warranty Terms & Conditions http://support.sf.fujitsu.com/warranty Wing June 2005 (Page 1000 Country) Warranty Terms & Conditions		
Protection: Short circuit, over current protection Efficiency: typical 96% at 100% load Connector and Cable Specification Input Connector: Ggarette lighter adapter with multiple connector system Input cable length: 100cm Upgut 2003 for 19V pin length: 14.2 + 0.5 mm; outer diameter: 5.5 mm Iyp C06 for 12V pin length: 100-+ 0.4 mm; outer diameter: 3.0 mm Output cable length: 100cm Output 2: USB receptacle, type A Color Black Device Classification Power consumption 85W + SW (USB) Power supply input 11 - 32V DC Power supply output 11 - 32V DC Power supply output 12V and 19V Devise Classification Europe Europe Europe Europe EC USA/Canada FCC Class B CUlus Austalla/New Zealand C-Tick Compliance link https://sp.ts.fujitsu.com/sites/certificates Miscellaneous Miscellaneous Dimensions (W x D x H) 15 x 53.7 x 21.5 mm Weight 250g w/o cables and connectors Order code Warranty period 2 years (depending on country) Warranty 1erms & Conditions http://support.sf.fujitsu.com/warranty Weight Graph Send-in Service (depending on country) Warranty 1erms & Conditions		0
Efficiency: typical 96% at 100% load Connector and Cable Specification Input connector: Ggarette lighter adapter with multiple connector system Input cable length: 100cm Output Connector: Upy C03 for 19V pin length: 14.2 + 0.5 mm; outer diameter: 3.5 mm Typ C03 for 19V pin length: 19.6 + -0.3 mm; outer diameter: 3.4 mm Typ C06 for 12V pin length: 10.0 + -0.4 mm; outer diameter: 3.0 mm Output cable length: 100cm Output 2: USB receptacle, type A Color Black Device Classification Power consumption 85W + 5W (USB) Power supply input 11 - 32V DC Power supply output 12V and 19V Devise Classification Europe CE USA/Canada CCIck Compliance link https://sp.us.fujitsu.com/sites/certificates Miscellaneous Dimensions (W x D x H) 115 x 53.7 x 21.5 mm Weight 250g w/o cables and connectors Order code Varianty period 2 years (depending on country) Warranty type 8 inty-//spending Service (depending on country) Warranty Terms & Conditions http://support.ts.fujitsu.com/swarranty		
Input cable length: 100cm Output Connector: Typ C03 for 19V pin length: 14.2 + 0.5 mm; outer diameter: 3.5 mm Typ C05 for 19V pin length: 10.0 + 0.4 mm; outer diameter: 3.4 mm Typ C06 for 12V pin length: 10.0 + 0.4 mm; outer diameter: 3.0 mm Output cable length: 100cm Output 2: USB receptacle, type A Color Black Device Classification Power consumption 85W + 5W (USB) Power supply input 11 - 32V DC Power supply output 12V and 19V Devise Classification Europe CE USA/Canada C-Tick Compliance link https://sp.ts.fujitsu.com/sites/certificates Miscellaneous Dimensions (W x D x H) 115 x 53.7 x 21.5 mm Weight 250g w/o cables and connectors Order code S26391+2613-L610 EAN: 4051554418304 Warranty period 8 ting-In / Send-In Service (depending on country) Warranty Terms & Conditions http://support.ts.fujitsu.com/warranty Warranty Terms & Conditions http://support.ts.fujitsu.com/warranty Warranty Terms & Conditions http://support.ts.fujitsu.com/warranty		
Output Connector: Typ (O3 for 19V pin length: 14.2 + 0.5 mm; outer diameter: 5.5 mm Typ (05 for 19V pin length: 9.6 + -0.3 mm; outer diameter: 3.4 mm Typ (05 for 12V pin length: 10.0 + -0.4 mm; outer diameter: 3.4 mm Typ (06 for 12V pin length: 10.0 + -0.4 mm; outer diameter: 3.0 mm Output cable length: 100cm Output 2: USB receptacle, type A Color Black Device Classification Power consumption 85W + 5W (USB) Power supply input 11 - 32V DC Power supply output 12V and 19V Devise Classification Europe CE USA/Canada FCC Class B cUlus Australia/New Zealand C-Tick Compliance link https://sp.ts.fujitsu.com/sites/certificates Miscellaneous Dimensions (W x D x H) 115 x 53.7 x 21.5 mm Weight 250g w/o cables and connectors Order code Varranty period 2 years (depending on country) Warranty type Bring-In Send-In Service (depending on country) Warranty Terms & Conditions	Connector and Cable Specification	Input Connector: Cigarette lighter adapter with multiple connector system
Typ C03 for 19V pin length: 14.2 + 0.5 mm; outer diameter: 3.5 mm Typ C05 for 19V pin length: 9.6 + -0.3 mm; outer diameter: 3.4 mm Typ C06 for 19V pin length: 10.0 + -0.4 mm; outer diameter: 3.0 mm Output cable length: 100cm Output 2: USB receptacle, type A Color Black Device Classification Power consumption 85W + 5W (USB) Power supply input 11 - 32V DC Power supply output 12 v and 19V Devise Classification Europe CE USA/Canada CCTick Compliance link https://sp.ts.fujitsu.com/sites/certificates Miscellaneous Miscellaneous Order code S26391-F2613-L610 EAN: 4051554418304 Warranty period 2 years (depending on country) Warranty Terms & Conditions http://support.ts.fujitsu.com/warranty Warranty Terms & Conditions http://support.ts.fujitsu.com/warranty ### Conditions ###		Input cable length: 100cm
Typ C03 for 19V pin length: 14.2 + 0.5 mm; outer diameter: 3.5 mm Typ C06 for 19V pin length: 9.6 + 0.3 mm; outer diameter: 3.4 mm Typ C06 for 19V pin length: 10.0 + 0.4 mm; outer diameter: 3.0 mm Output cable length: 100cm Output 2: USB receptacle, type A Color Black Device Classification Power consumption 85W + 5W (USB) Power supply input 11 - 32V DC Power supply output 12V and 19V Devise Classification Europe E USA/Canada FCC Class B cULus Australia/New Zealand C-Tick Compliance link https://sp.ts.fujitsu.com/sites/certificates Miscellaneous Miscellaneous Dimensions (W x D x H) 115 x 53.7 x 21.5 mm Weight 250g w/o cables and connectors Order code S26391-F2613-L610 EAN: 4051554418304 Warranty period 2 years (depending on country) Warranty type Bring-In / Service (depending on country) Warranty Terms & Conditions		Output Connector:
Typ C06 for 12V pin length: 10.0 + 0.4 mm; outer diameter: 3.0 mm Output cable length: 100cm Output 2: USB receptacle, type A Color Black Device Classification Power consumption 85W + 5W (USB) Power supply input 11 - 32V DC Power supply output 12V and 19V Devise Classification Europe CE USA/Canada CCTick Compliance link https://sp.ts.fujitsu.com/ssites/certificates Miscellaneous Dimensions (W x D x H) 115 x 53.7 x 21.5 mm Weight 250g w/o cables and connectors Order code Varranty period 2 years (depending on country) Warranty Terms & Conditions		Typ CO3 for 19V pin length: 14.2 + 0.5 mm; outer diameter: 5.5 mm
Color Black Color Black Color Black Device Classification Power consumption 85W + 5W (USB) Power supply input 11 - 32V DC Power supply output 12V and 19V Devise Classification Europe CE USA/Canada C-Tick Compliance link https://sp.ts.fujitsu.com/sites/certificates Miscellaneous Dimensions (W x D x H) 115 x 53.7 x 21.5 mm Weight 250g w/o cables and connectors Order code Varranty period 2 years (depending on country) Warranty Terms & Conditions Australiary New Zender Schooltions Dimensions (W x D x H) 115 x 53.7 is pind-in Service (depending on country) Warranty Terms & Conditions Nttp://support.ts.fujitsu.com/warranty		
Color Black Device Classification Power consumption 85W + 5W (USB) Power supply input 11 - 32V DC Power supply output 12V and 19V Devise Classification Europe CE USA/Canada FCC Class B cUlus Australia/New Zealand C-Tick Compliance link https://sp.ts.fujitsu.com/sites/certificates Miscellaneous Dimensions (W x D x H) 115 x 53.7 x 21.5 mm Weight 250g w/o cables and connectors Order code Order code S26391-F2613-L610 EAN: 4051554418304 Warranty period 2 years (depending on country) Warranty type Bring-In / Send-In Service (depending on country) Warranty Terms & Conditions http://support.ts.fujitsu.com/warranty		
Device Classification Power consumption 85W + 5W (USB) Power supply input 11 - 32V DC Power supply output 12V and 19V Devise Classification Europe CE USA/Canada FCC Class B cULus Australia/New Zealand C-Tick Compliance link https://sp.ts.fujitsu.com/sites/certificates Miscellaneous Dimensions (W x D x H) 115 x 53.7 x 21.5 mm Weight 250g w/o cables and connectors Order code S26391-F2613-L610 EAN: 4051554418304 Warranty period 2 years (depending on country) Warranty type Bring-In / Send-In Service (depending on country) Warranty Terms & Conditions http://support.ts.fujitsu.com/warranty		
Power consumption 85W + 5W (USB) Power supply input 11 - 32V DC Power supply output 12V and 19V Devise Classification Europe CE USA/Canada FCC Class B cULus Australia/New Zealand C-Tick Compliance link https://sp.ts.fujitsu.com/sites/certificates Miscellaneous bittps://sp.ts.fujitsu.com/sites/certificates Dimensions (W x D x H) 115 x 53.7 x 21.5 mm Weight 250g w/o cables and connectors Order code S26391-F2613-L610 EAN: 4051554418304 Warranty period 2 years (depending on country) Warranty type Bring-In / Send-In Service (depending on country) Warranty Terms & Conditions http://support.ts.fujitsu.com/warranty	Color	Black
Power supply input 11 - 32V DC Power supply output 12V and 19V Devise Classification Europe CE USA/Canada FCC Class B cULus Australia/New Zealand C-Tick Compliance link https://sp.ts.fujitsu.com/sites/certificates Miscellaneous Dimensions (W x D x H) 115 x 53.7 x 21.5 mm Weight 250g w/o cables and connectors Order code S26391-F2613-L610 EAN: 4051554418304 Warranty period 2 years (depending on country) Warranty type Bring-In / Send-In Service (depending on country) Warranty Terms & Conditions http://support.ts.fujitsu.com/warranty	Device Classification	
Power supply output 12V and 19V Devise Classification Europe CE USA/Canada FCC Class B cUlus Australia/New Zealand C-Tick Compliance link https://sp.ts.fujitsu.com/sites/certificates Miscellaneous Dimensions (W x D x H) 115 x 53.7 x 21.5 mm Weight 250g w/o cables and connectors Order code S26391-F2613-L610 EAN: 4051554418304 Warranty period 2 years (depending on country) Warranty type Bring-In / Send-In Service (depending on country) Warranty Terms & Conditions http://support.ts.fujitsu.com/warranty	Power consumption	85W + 5W (USB)
Devise Classification Europe CE USA/Canada FCC Class B cUl.us Australia/New Zealand C-Tick Compliance link https://sp.ts.fujitsu.com/sites/certificates Miscellaneous Dimensions (W x D x H) 115 x 53.7 x 21.5 mm Weight 250g w/o cables and connectors Order code S26391-F2613-L610 EAN: 4051554418304 Warranty period 2 years (depending on country) Warranty type Bring-In / Send-In Service (depending on country) Warranty Terms & Conditions http://support.ts.fujitsu.com/warranty	Power supply input	11 - 32V DC
Europe USA/Canada FCC Class B cULus Australia/New Zealand C-Tick Compliance link https://sp.ts.fujitsu.com/sites/certificates Miscellaneous Dimensions (W x D x H) 115 x 53.7 x 21.5 mm Weight 250g w/o cables and connectors Order code S26391-F2613-L610 EAN: 4051554418304 Warranty period 2 years (depending on country) Warranty type Bring-In / Send-In Service (depending on country) Warranty Terms & Conditions http://support.ts.fujitsu.com/warranty	Power supply output	12V and 19V
USA/Canada FCC Class B cULus Australia/New Zealand C-Tick Compliance link https://sp.ts.fujitsu.com/sites/certificates Miscellaneous Dimensions (W x D x H) 115 x 53.7 x 21.5 mm Weight 250g w/o cables and connectors Order code S26391-F2613-L610 EAN: 4051554418304 Warranty period 2 years (depending on country) Warranty type Bring-In / Send-In Service (depending on country) Warranty Terms & Conditions http://support.ts.fujitsu.com/warranty	Devise Classification	
CULusAustralia/New ZealandC-TickCompliance linkhttps://sp.ts.fujitsu.com/sites/certificatesMiscellaneousI15 x 53.7 x 21.5 mmDimensions (W x D x H)115 x 53.7 x 21.5 mmWeight250g w/o cables and connectorsOrder codeS26391-F2613-L610EAN: 4051554418304Warranty period2 years (depending on country)Warranty typeBring-In / Send-In Service (depending on country)Warranty Terms & Conditionshttp://support.ts.fujitsu.com/warranty	Europe	CE
Australia/New Zealand Compliance link https://sp.ts.fujitsu.com/sites/certificates Miscellaneous Dimensions (W x D x H) 115 x 53.7 x 21.5 mm Weight 250g w/o cables and connectors Order code S26391-F2613-L610 EAN: 4051554418304 Warranty period 2 years (depending on country) Warranty type Bring-In / Send-In Service (depending on country) Warranty Terms & Conditions http://support.ts.fujitsu.com/warranty	USA/Canada	
Compliance link https://sp.ts.fujitsu.com/sites/certificates Miscellaneous Dimensions (W x D x H) 115 x 53.7 x 21.5 mm Weight 250g w/o cables and connectors Order code S26391-F2613-L610 EAN: 4051554418304 Warranty period 2 years (depending on country) Warranty type Bring-In / Send-In Service (depending on country) Warranty Terms & Conditions http://support.ts.fujitsu.com/warranty	Australia/Now 70 aland	
Miscellaneous Dimensions (W x D x H) 115 x 53.7 x 21.5 mm Weight 250g w/o cables and connectors Order code S26391-F2613-L610 EAN: 4051554418304 Warranty period 2 years (depending on country) Warranty type Bring-In / Send-In Service (depending on country) Warranty Terms & Conditions http://support.ts.fujitsu.com/warranty		
Dimensions (W x D x H) Weight 250g w/o cables and connectors Order code S26391-F2613-L610 EAN: 4051554418304 Warranty period 2 years (depending on country) Warranty type Bring-In / Send-In Service (depending on country) Warranty Terms & Conditions http://support.ts.fujitsu.com/warranty	•	1 1 , 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
Weight 250g w/o cables and connectors Order code S26391-F2613-L610 EAN: 4051554418304 Warranty period 2 years (depending on country) Warranty type Bring-In / Send-In Service (depending on country) Warranty Terms & Conditions http://support.ts.fujitsu.com/warranty		115 x 53.7 x 21.5 mm
Order code S26391-F2613-L610 EAN: 4051554418304 Warranty period 2 years (depending on country) Warranty type Bring-In / Send-In Service (depending on country) Warranty Terms & Conditions http://support.ts.fujitsu.com/warranty		
S26391-F2613-L610 EAN: 4051554418304 Warranty period 2 years (depending on country) Warranty type Bring-In / Send-In Service (depending on country) Warranty Terms & Conditions http://support.ts.fujitsu.com/warranty		<u> </u>
Warranty type Bring-In / Send-In Service (depending on country) Warranty Terms & Conditions http://support.ts.fujitsu.com/warranty		S26391-F2613-L610 EAN: 4051554418304
Warranty type Bring-In / Send-In Service (depending on country) Warranty Terms & Conditions http://support.ts.fujitsu.com/warranty	Warranty period	2 years (depending on country)
Warranty Terms & Conditions http://support.ts.fujitsu.com/warranty		
	•	

More information

Fujitsu products, solutions & services

In addition to FUJITSU Accessory Car Truck Power Adapter 90, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about FUJITSU Accessory Car Truck Power Adapter 90, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website. www.fujitsu.com/fts/accessories

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at http://www.fujitsu.com/global/about/environment



Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html

Copyright 2018 Fujitsu Technology Solutions GmbH

Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

Fujitsu Technology Solutions GmbH Website: www.fujitsu.com/fts 2018-07-04 EM-EN All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html
Copyright 2018 Fujitsu Technology Solutions GmbH