

## Product Image



/publicpictures/Produktbild/1171960205.tif

## Master data

|                           |                       |
|---------------------------|-----------------------|
| Product number:           | 1171960205            |
| EAN:                      | 4007123675685         |
| Artikelverantwortlicher:  | Brennenstuhl Tübingen |
| manufacturer:             | Brennenstuhl          |
| Product line:             | EL                    |
| Kundenspezifisch:         | No                    |
| Minimalpflege:            | No                    |
| Ausleitungskennzeichen:   | J                     |
| Gewählte Vertriebsregion: | De                    |
| Gewählte Sprache:         | en                    |

## Texts

### Is4-Bezeichnung 1/2:

Mobiler LED Akku Strahler EL 2000 MA 2150lm, IP54, USB Kabel, 20W

### Short description for the internet:

Brennenstuhl LED Work Light Rechargeable EL 2000 MA / Portable Floodlight 20W for Indoor and Outdoor Use IP54 (Job Site Light 2150lm with Integrated Li-Ion Battery, Powerbank Function, up to 6h Light Duration)

### Website-Kurztext:

Rechargeable LED Work Light EL 2000 MA 20W for Indoors and Outdoors IP54 (Job Site Light 2150lm with 2 Switching Levels and Powerbank Function, up to 6h Light Duration, with Low-Battery Warning, Space-saving due to Foldable Frame)

### Print-Kurztext:

Rechargeable LED Work Light EL 2000 MA 2150lm, IP54

### Bulletpoint 1:

Extremely compact and lightweight LED Work Light Rechargeable with an output of 20 W is ideally suited for outdoor use thanks to the IP54 protection rating (dust and splash-proof)

### Bulletpoint 2:

Compact Job Site Lighting with integrated Li-Ion battery (3,7 V/6,6A h) can be easily folded for transport or storage - a space-saving and handy light source to take along

### Bulletpoint 3:

Portable Floodlight with 2150 lm has two switching levels (100%, 50% light) - perfect to adjust the work light according to the requirements and needs

### Bulletpoint 4:

Continuously swivelling portable battery security light shines for up to 6 h at 50% light output - also with practical battery status display and additional low-battery warning

### Bulletpoint 5:

Scope of delivery: 1x LED Work Light EL 2000 MA with 20 W power and additional powerbank function (1 A), 1x USB charging cable - in best brennenstuhl® quality

### Online-Beschreibung:

The rechargeable EL 2000 MA LED Work Light from Brennenstuhl is a compact LED Job Site Light with 20 W power that can be used both indoors and outdoors. It can be easily folded for transport or storage and is therefore very handy and space-saving at the same time. In addition, the portable Floodlight convinces with the following features:

- \* Switch with dimmer function 100% / 50%
- \* With power bank 5V/1A
- \* Suitable for mounting on brennenstuhl® tripods
- \* Power: 20 W
- \* Luminous flux: 2150 lumen
- \* Battery: Li-Ion 3,7 V / 6,6 Ah
- \* Light duration 3 h (100%) / 6 h (50%)
- \* Charging time approx. 4 h
- \* Colour temperature: 6000K
- \* Protection class IP54: dust- and splash-proof
- \* IK08

#### Website description:

The rechargeable LED Work Light EL 2000 MA with 20 W power is suitable for use both indoors and outdoors thanks to the IP54 protection class (dust and splash-proof), such as for various DIY and craftsmen's work that takes place in or around the house. The portable Floodlight can be continuously swivelled and locked in place and can be stored and transported in a space-saving way thanks to its foldable frame. Not only the aluminium housing is extremely robust, but also the stable tubular steel frame and the locking screws. In addition, the rechargeable Spotlight convinces with the following features:

- \* Suitable for mounting on brennenstuhl® tripods
- \* Power: 20 W
- \* Luminous flux: 2150 lumen
- \* Battery: Li-Ion 3,7 V / 6,6 Ah
- \* Max. Lighting duration: 6 h
- \* Colour temperature: 6000 K
- \* Protection class IP54: dust- and splash-proof
- \* IK08

#### Schlagworte:

job site lighting, work light rechargeable, portable work light with stand, job site lighting, work light 20w, rechargeable work light with stand, rechargeable work light led, rechargeable work light brennenstuhl, rechargeable work light 20w, portable floodlight, portable floodlight rechargeable, portable floodlight and stand, portable floodlight 20w

#### Subtitle:

For indoor and outdoor use, IP 54.

#### Print-Beschreibung:

- \* Solid, modern aluminium housing.
- \* Space-saving due to foldable frame.
- \* Switch with dimmer function 100% / 50%.
- \* Sturdy tubular steel frame with plastic protective corners and ergonomically shaped plastic carrying handle.
- \* Spotlight can be steplessly swivelled and locked.
- \* Suitable for mounting on brennenstuhl® tripods.
- \* With integrated Li-Ion battery 3,7 V / 6,6 Ah and battery status display on the back and additional low-battery warning.
- \* Includes powerbank function and 1x USB charging cable.

#### Infotext:

#### Table article information:

#### Scope of supply:

## Media



/publicpictures/icon/icon-leuchtdauer-6h-max.eps



/publicpictures/icon/icon-stecksystem-usb-powerbank.eps



/publicpictures/icon/icon-stecksystem-usb-rechargeable.eps



/publicpictures/icon/icon-schutzart-ip54.eps



/publicpictures/icon/icon-stossfest-ik08.eps



/publicpictures/icon/icon-lumen-2150.eps



/publicpictures/Detailansicht/1171960205-frontansicht.tif



/publicpictures/Detailansicht/1171960205-seitenansicht.tif



/publicpictures/Detailansicht/1171960205-seitenansicht-mehrfach.tif



/publicpictures/Detailansicht/1171960205-seitenansicht-zusammengeklappt.tif



/publicpictures/Detailansicht/1171960205-hinten.tif



/publicpictures/Detailansicht/1171960205-laden.tif



/publicpictures/Anwendung/1171960205-anwendung-baustelle-hinten-1.tif



/publicpictures/Anwendung/1171960205-anwendung-baustelle-tragend.tif



/publicpictures/Anwendung/1171960205-anwendung-baustelle-5.tif



/publicpictures/Anwendung/1171960205-anwendung-baustelle-6.tif

/restrictedpictures/QR-Code/1171960205-qr-code-info.eps

## Context

|                    |               |                   |
|--------------------|---------------|-------------------|
| Attributkategorie: | Light         | Accessories:      |
| Garantie:          | Other (legal) | Ersatzteil:       |
|                    |               | Similar products: |

## Technical data

|                                  |                       |  |                     |
|----------------------------------|-----------------------|--|---------------------|
| <b>Batterie</b>                  |                       | Degree of protection (IP):                             | IP54                |
| Battery type:                    | Built-in battery pack | Suitable for outdoor area:                             | Yes                 |
| Battery technology:              | Lithium-ion           | Impact strength:                                       | IK08                |
| Rechargeable:                    | Yes                   | Shock resistance:                                      | Yes                 |
| Number of cells:                 | 3                     | Watertight:  | No                  |
| Light duration:                  | 6h                    | Min. operation temperature:                            | -10°C               |
| Capacity:                        | 6.6Ah                 | Max. operation temperature:                            | 40°C                |
| Voltage:                         | 3.7V                  | <b>Leuchte3Stecksystem</b>                             |                     |
| IEC indication:                  | Other                 | With usb output:                                       | Yes                 |
| Other indications:               | Without               | Load input:  | Yes                 |
| Einsatz im Ex-Bereich - ep:      | No                    | USB-Cable length:                                      | 1m                  |
| With battery charging indicator: | Yes                   | <b>Leuchtmittel0Allgemein</b>                          |                     |
| With battery status indicator:   | Yes                   | Lamp type:   | LED non-replaceable |
| With backup battery:             | No                    | <b>Leuchtmittel1Betriebseigenschaften</b>              |                     |
| Backup battery included:         | Without               | Life time of light:                                    | 36,000h             |
| Traction battery:                | No                    | E c (kWh) (= rated energy consumption in 1,000 hours): | 20kWh               |
| Power:                           | 24.42Wh               | Colour rendering index CRI:                            | 80-89 (class 1B)    |
| Loading current:                 | 2,200mA               | Colour temperature:                                    | 6,000K              |
| Charging time:                   | 4h                    | Adjustable colour temperature:                         | No                  |
| <b>Leuchte0Allgemein</b>         |                       | Colour of light - ep:                                  | 860                 |
| Type of lamp:                    | Floodlight            | Fluorescent colour:                                    | white               |
| Model:                           | Not applicable        | Multicolour- switch steps:                             | No                  |
| Housing material:                | Metal                 | Adjustable luminous flux:                              | No                  |
| Halogen free:                    | Yes                   | Total luminous flux:                                   | 2,150lm             |

|   |              |  |           |
|---|--------------|--|-----------|
| Housing colour:                               | black, grey  | <b>Netzteil</b>                          |           |
| Colour cover:                                 | transparent  | externes Netzteil:                       | No        |
| Colour:                                       | silver, grey | Optionales externes Netzteil verfügbar:  | No        |
| Lamp type included:                           | Yes          | Output voltage:                          | 5V        |
| Number of lamps:                              | 30           | Output current:                          | 1A        |
| Number of batteries:                          | 1            | With power supply:                       | No        |
| Battery included:                             | Yes          | Type of plug - Output:                   | Micro USB |
| Direction of rotation:                        | Horizontal   | With charge cable:                       | Yes       |
| Rotatable - ep:                               | Yes          | <b>Mgv</b>                               |           |
| Collapsible/ Bendable:                        | Yes          | Packaging unit (UP):                     | 1         |
| With carrying handle:                         | Yes          | Weight of product (without packaging):   | 1.13kg    |
| With turn handle:                             | No           | Length of product (without packaging):   | 7cm       |
| Integrated magnet:                            | No           | Width of product (without packaging):    | 25.2cm    |
| Height adjustable:                            | No           | Height of product (without packaging):   | 26cm      |
| With loudspeaker:                             | No           | Weight of product (including packaging): | 1.3kg     |
| With radio:                                   | No           | Length of product (including packaging): | 7.8cm     |
| With frame:                                   | Yes          | Width of product (including packaging):  | 26cm      |
| With tripod holder:                           | Yes          | Height of product (including packaging): | 27cm      |
| With ground spike:                            | No           |  |           |
| With protective grille:                       | No           |  |           |
| With pocket torch function:                   | No           |  |           |
| Focus:  | No           |  |           |
| Laserpointer:                                 | No           |  |           |
| Nippelgewinde - ep:                           | Without      |  |           |
| With quick-acting facility:                   | Yes          |  |           |
| With air slots:                               | No           |  |           |
| Colour controllable (RGB):                    | No           |  |           |
| Direct/ indirect parts separately adjustable: | No           |  |           |
| Packaging:                                    |              |  |           |
| E c:  | 20kWh        |  |           |
| Fluorescent colour:                           | white        |  |           |

|                                       |                      |
|---------------------------------------|----------------------|
| Adjustable colour temperature:        | No                   |
| Adjustable luminous flux:             | Levels               |
| Luminous flux:                        | 2,150lm              |
| Suitable for emergency lighting:      | No                   |
| Emergency unit integrated:            | No                   |
| With orientation lighting:            | No                   |
| Suitable for accent lighting:         | No                   |
| Fit for monitor workplace:            | No                   |
| Multicolour- switch steps:            | No                   |
| <b>Leuchte1elektrWerte</b>            |                      |
| Protection class:                     | III                  |
| Power supply:                         | Rechargeable battery |
| Load input for external power supply: | Yes                  |
| Output voltage:                       | 5V                   |
| Type of output voltage:               | Direct voltage (DC)  |
| Type of input voltage:                | Direct voltage (DC)  |
| Max. output current USB:              | 1A                   |
| <b>Leuchte2Anwendung</b>              |                      |
| With on/off switch:                   | Yes                  |
| Illuminated switch:                   | No                   |
| With twilight switch:                 | No                   |

## Variantgroup

Rechargeable LED Work Light EL 2000 MA

- \* Solid, modern aluminium housing.
- \* Space-saving due to foldable frame.
- \* Switch with dimmer function 100% / 50%.
- \* Sturdy tubular steel frame with plastic protective corners and ergonomically shaped plastic carrying handle.
- \* Spotlight can be steplessly swivelled and locked.
- \* Suitable for mounting on brennenstuhl® tripods.
- \* With integrated Li-Ion battery 3,7 V / 6,6 Ah and battery status display on the back and additional low-battery warning.
- \* Includes powerbank function and 1x USB charging cable.

### Related Article

1171960205



**Variant Differentiation**