

Product Image



/publicpictures/Produktbild/1173070010.tif

Master data

Product number:	1173070010
EAN:	4007123674442
Artikelverantwortlicher:	Brennenstuhl Tübingen
manufacturer:	Brennenstuhl
Product line:	CL
Kundenspezifisch:	No
Minimalpflege:	No
Ausleitungskennzeichen:	J
Gewählte Vertriebsregion:	De
Gewählte Sprache:	en

Texts

Is4-Bezeichnung 1/2:

Mob. LED Akku Strahler CL 1050 MA Clip, IP65, 950lm

Short description for the internet:

Brennenstuhl Mobile LED Battery Spotlight CL 1050 MA / Clampable LED Work Light 10W with Clamping Device (LED Construction Spotlight with Tilt Angle, USB, Powerbank, 950lm, IP65, Engineered in Germany)

Website-Kurztext:

Mobile LED rechargeable spotlight CL 1050 MA / clampable LED work spotlight 10W (LED construction spotlight with clamping device ideally suited for work of home and craftsmen, in workshops or on assembly, 950lm, 12h burn time, Engineered in Germany)

Print-Kurztext:

LED battery spotlight CL 1050 MA Clip, 950lm, IP65

Bulletpoint 1:

LED work light with clamping device for more flexibility and functions, thanks to a clamping width of up to 55mm, for the work of home and craftsmen, in workshops or on assembly

Bulletpoint 2:

Simple and individual alignment of the working light thanks to ball bearing, the angle of inclination of the working light can be flexibly adjusted in all directions by almost 360°

Bulletpoint 3:

LED work spotlight with 3 switching levels (100% - 50% - 25%) for a light duration of up to 12h and integrated USB powerbank for charging devices with USB charging cable like smartphones, tablets, etc.

Bulletpoint 4:

Robust LED construction spotlight 10W with break- and impact-resistant housing - with integrated Li-ion battery (3,7 V/2,5 Ah), charging indicator and USB cable type A/C

Bulletpoint 5:

Scope of delivery : 1 x mobile LED battery-powered floodlight CL 1050 MA 10W (950lm) incl. Li-Ion battery (3,7 V/2,5 Ah), 1 x USB cable type A/C - best quality by brennenstuhl®

Online-Beschreibung:

The mobile rechargeable LED work light CL 1050 MA by Brennenstuhl convinces with more flexibility and functions for the versatile work use of home and craftsmen in

workshops or on assembly. Thanks to the special clamping device, the compact LED work light can be attached to work surfaces, pipes, plates, etc. without much effort and thus offers a bright, glare-free light and free hands when working. Thanks to the ball bearing and the integrated ball joint, the inclination angle of the LED construction light can be flexibly adjusted by almost 360° and individually aligned in all directions. In addition, the LED work light convinces with the following features

- * Working light with bright SMD-LEDs
- * Li-Ion battery 3,7V/2,5Ah with charge indicator
- * Light duration up to 12h
- * With integrated USB power bank
- * USB charging cable type A/C
- * Break and impact resistant housing
- * Light and robust plastic housing
- * Stable clip system for mounting up to 55mm diameter
- * Dustproof and jet water protected, IP65
- * Switching levels: 100% / 50% / 25%
- * Colour temperature: 6350 K
- * Luminous flux: 950lm
- * Protection class: IK08
- * Category 2 (K2) equipment: for use in harsh environments with high mechanical, physical and chemical loads

Website description:

The mobile rechargeable LED work light CL 1050 MA convinces with more flexibility and functions for the versatile work of home and craftsmen in workshops or on assembly. Thanks to the stable clip system (clamping width up to 55mm), the compact LED work light can be attached to work surfaces, pipes, plates, etc. without much effort and thus offers a bright, glare-free light and free hands when working. The three switching levels (100% / 50% / 25%) allow individually adapted illumination. The break- and impact-resistant plastic housing protects the LED spotlight from damage and offers IP65 protection (dustproof & jet-proof). Thanks to the ball bearing and the integrated ball joint, the tilt angle of the LED construction spotlight can be flexibly adjusted by almost 360° and individually aligned in all directions. In addition, the work light equipped with SMD LEDs convinces with the following features:

- * Li-Ion battery 3.7V/2.5Ah with charge indicator
- * Light duration up to 12h
- * With integrated USB Powerbank
- * USB charging cable type A/C
- * Color temperature: 6350 K
- * Luminous flux: 950lm
- * Protection class: IK08
- * Category 2 (K2) equipment: For use in harsh environments with high mechanical, physical and chemical impact

Schlagworte:

Subtitle:

The work spotlights with clamping device can be attached anywhere and optimally aligned for the work application thanks to the ball joint.

Print-Beschreibung:

- * Ideally suited for assembly work, in cellars and on workbenches.
- * Work spotlight with special clamping device for easy mounting by clamping to work surfaces, pipes, panels, etc.
- * Lightweight and robust plastic housing with strong, sturdy clip.
- * Easy alignment of the working light thanks to ball bearing, the angle of inclination of the working light is flexibly adjustable.
- * With ball joint for individual alignment in all directions by almost 360 degrees.
- * Integrated USB power bank for charging smartphones etc.
- * Li-Ion battery 3.7V/2.5Ah with charging indicator.
- * Light duration up to 12h, charging time approx. 3h.
- * Category 2 (K2) equipment: Use for rough operation with high mechanical, physical and chemical effects.

Infotext:

Table article information:

Scope of supply:

Media



/publicpictures/Logo-Brennenstuhl/logo-engineered-in-germany.eps



/publicpictures/lcon/icon-norm-bgi-608-k2.eps



/publicpictures/lcon/icon-stossfest-ik08.eps



/publicpictures/lcon/icon-leuchtdauer-12h-max.eps



/publicpictures/lcon/icon-stecksystem-usb-powerbank.eps



/publicpictures/lcon/icon-schutzart-ip65.eps



/publicpictures/lcon/icon-lumen-950.eps



/publicpictures/Detailansicht/1173070010-perspektive.tif



/publicpictures/Detailansicht/1173070010-frontansicht.tif



/publicpictures/Detailansicht/1173070010-seitenansicht.tif



/publicpictures/Detailansicht/1173070010-hinten.tif



/publicpictures/Detailansicht/1173070010-ladezustand-usb.tif



/publicpictures/Detailansicht/1173070010-klemmbuegel-stange.tif



/publicpictures/Anwendung/1173070020-ambiente-kfz-werkstatt-lackiererei.tif



/publicpictures/Anwendung/1173070020-anwendung-kfz-werkstatt-werkbank-smartphone-laden.tif



/publicpictures/Anwendung/1173070010-anwendung-kfz-werkstatt-hebebiehne-1.tif




/publicpictures/Anwendung/1173070010-anwendung-baustelle-sanitaer-klemmbuegel-3.tif




/publicpictures/Anwendung/1173070010-anwendung-sicherungskasten-klemmbuegel.tif



/publicpictures/Anwendung/1173070010-anwendung-baustelle-festklemmen-1.tif



/publicpictures/Anwendung/1173070010-anwendung-baustelle-klemmbuegel.tif



/publicpictures/Anwendung/1173070010-anwendung-baustelle-festklemmen-2.tif

/restrictedpictures/QR-Code/1173070010-qr-code-info.eps

Context

Attributkategorie:

Light

Accessories:

Garantie:

Other (legal)

Ersatzteil:

Similar products:

Technical data

Batterie		Degree of protection (IP):	IP65
Battery type:	Built-in battery pack	Suitable for outdoor area:	Yes
Battery technology:	Lithium-ion	Impact strength:	IK08
Rechargeable:	Yes	Shock resistance:	Yes
Replaceable:	No	Watertight:	No
Number of cells:	1	Min. operation temperature:	-10°C
Light duration:	12h	Max. operation temperature:	40°C
Capacity:	2.5Ah	Leuchte3Stecksystem	
Voltage:	3.7V	With socket outlet:	No
With battery charging indicator:	Yes	With usb output:	Yes
With battery status indicator:	Yes	Type of plug - Input:	USB
Backup battery included:	Without	Load input:	Yes
Power:	9.25Wh	USB-Cable length:	1m
Loading current:	1,000mA	Leuchte4Details	
Charging time:	3h	For "complicated conditions" (according to VDE):	Yes
Leuchte0Allgemein		Leuchtmittel0Allgemein	
Type of lamp:	Floodlight	Lamp type:	LED non-replaceable
Reflector:	Matt	Leuchtmittel1Betriebseigenschaften	
Housing material:	Plastic	Life time of light:	51,000h
Surface:	Other	Colour rendering index CRI:	80-89 (class 1B)
Surface finishing:	Matt	Colour temperature:	6,350K
Halogen free:	Yes	Adjustable colour temperature:	No
Housing colour:	black	Fluorescent colour:	white
Colour cover:	white	Adjustable luminous flux:	Levels
Colour:	black	Total luminous flux:	950lm
Lamp type included:	Yes	Netzteil	
Number of lamps:	27	Output voltage:	5V
Number of batteries:	1	Output current:	1A
Battery included:	Yes	With power supply:	No
Rotatable - ep:	Yes	With charge cable:	Yes

Collapsible/ Bendable:	Yes	Min. nominal voltage at charge cable:	5V
Packaging:		Mgv	
Adjustable colour temperature:	No	Packaging unit (UP):	1
Adjustable luminous flux:	Levels	Weight of product (without packaging):	0.4kg
Luminous flux:	950lm	Length of product (without packaging):	9cm
Suitable for emergency lighting:	No	Width of product (without packaging):	8.5cm
Emergency unit integrated:	No	Height of product (without packaging):	18cm
With orientation lighting:	No	Weight of product (including packaging):	0.53kg
Suitable for accent lighting:	No	Length of product (including packaging):	10cm
Fit for monitor workplace:	No	Width of product (including packaging):	10cm
Multicolour- switch steps:	No	Height of product (including packaging):	18.7cm

Leuchte1elektrWerte

Protection class:	III
Power supply:	Rechargeable battery
Load input for external power supply:	Yes
Power consumption:	10W
Output voltage:	5V
Nominal input voltage:	5V
Type of output voltage:	Direct voltage (DC)
Type of input voltage:	Alternating voltage (AC)
Max. output current USB:	1A

Leuchte2Anwendung

With on/off switch:	Yes
With twilight switch:	No

Variantgroup

LED battery spotlight CL with clamping device

- * Ideally suited for assembly work, in cellars and on workbenches.
- * Work spotlight with special clamping device for easy mounting by clamping to work surfaces, pipes, panels, etc.
- * Lightweight and robust plastic housing with strong, sturdy clip.
- * Easy alignment of the working light thanks to ball bearing, the angle of inclination of the working light is flexibly adjustable.
- * With ball joint for individual alignment in all directions by almost 360 degrees.



* Integrated USB power bank for charging smartphones etc.

* Category 2 (K2) equipment: For use in harsh environments with high mechanical, physical and chemical impact.

Related Article

1173070010

1173070020

Variant Differentiation

Objektbrick Leuchtmittel1Betriebeigenschaften: Attribut max_luminous_flux