

Product Image



/publicpictures/Produktbild/1173070020.tif

Master data

Product number:	1173070020
EAN:	4007123674459
Artikelverantwortlicher:	Brennenstuhl Tübingen
manufacturer:	Brennenstuhl
Product line:	CL
Kundenspezifisch:	No
Minimalpflege:	No
Ausleitungskennzeichen:	J
Gewählte Vertriebsregion:	De
Gewählte Sprache:	en

Texts

Is4-Bezeichnung 1/2:

Mob. LED Akku Strahler CL 4050 MA Clip, IP65, 3800lm

Short description for the internet:

Brennenstuhl Mobile LED Battery Spotlight CL 4050 MA / Clampable LED Work Light 40W with Clamping Device (LED Construction Spotlight with Tilt Angle, USB, Powerbank, 3800lm, IP65, Engineered in Germany)

Website-Kurztext:

Mobile LED rechargeable spotlight CL 4050 MA / clampable LED work spotlight 40W (LED construction spotlight with clamping device ideally suited for work of home and craftsmen, in workshops or on assembly, 3800lm, 12h burn time, Engineered in Germany)

Print-Kurztext:

LED battery spotlight CL 4050 MA Clip, 3800lm, IP65

Bulletpoint 1:

LED work light with clamping device for more flexibility and functions, thanks to a clamping width of up to 55mm, for the work of home and craftsmen, in workshops or on assembly

Bulletpoint 2:

Simple and individual alignment of the working light thanks to ball bearing, the angle of inclination of the working light can be flexibly adjusted in all directions by almost 360°

Bulletpoint 3:

LED work spotlight with 3 switching levels (100% - 50% - 25%) for a light duration of up to 12h and integrated USB powerbank for charging devices with USB charging cable like smartphones, tablets, etc.

Bulletpoint 4:

Robust LED construction spotlight 40W with break- and impact-resistant housing - with integrated Li-ion battery (7,4 V/5 Ah), charging indicator and USB cable type A/

Bulletpoint 5:

Scope of delivery : 1 x mobile LED battery-powered floodlight CL 4050 MA 40W (3800lm) incl. Li-Ion battery (7,4 V/5.0 Ah), 1 x USB cable type A/C - best quality by brennenstuhl®

Online-Beschreibung:

The mobile rechargeable LED work light CL 4050 MA by Brennenstuhl convinces with more flexibility and functions for the versatile work use of home and craftsmen in workshops or on assembly. Thanks to the special clamping device, the compact LED work light can be attached to work surfaces, pipes, plates, etc. without much effort

and thus offers a bright, glare-free light and free hands when working. Thanks to the ball bearing and the integrated ball joint, the inclination angle of the LED construction light can be flexibly adjusted by almost 360° and individually aligned in all directions. In addition, the LED work light convinces with the following features

- * Working light with bright SMD-LEDs
- * Li-Ion battery 7.4 V/5.0 Ah with charge indicator
- * Light duration up to 12h
- * With integrated USB power bank
- * USB charging cable type A/C
- * Break and impact resistant housing
- * Light and robust plastic housing
- * Stable clip system for mounting up to 55mm diameter
- * Dustproof and jet water protected, IP65
- * Switching levels: 100% / 50% / 25%
- * Colour temperature: 6350 K
- * Luminous flux: 3800lm
- * Protection class: IK08
- * Category 2 (K2) equipment: for use in harsh environments with high mechanical, physical and chemical stresses

Website description:

The mobile rechargeable LED work light CL 4050 MA convinces with more flexibility and functions for the versatile work of home and craftsmen in workshops or on assembly. Thanks to the stable clip system (clamping width up to 55mm), the compact LED work light can be attached to work surfaces, pipes, plates, etc. without much effort and thus offers a bright, glare-free light and free hands when working. The three switching levels (100% / 50% / 25%) allow individually adapted illumination. The break- and impact-resistant plastic housing protects the LED spotlight from damage and offers IP65 protection (dustproof & jet-proof). Thanks to the ball bearing and the integrated ball joint, the tilt angle of the LED construction spotlight can be flexibly adjusted by almost 360° and individually aligned in all directions. In addition, the work light equipped with SMD LEDs convinces with the following features:

- * Li-Ion battery 7.4 V/5.0 Ah with charge indicator
- * Light duration up to 12h
- * With integrated USB Powerbank
- * USB charging cable type A/C
- * Colour temperature: 6400 K
- * Luminous flux: 3800lm
- * Protection class: IK08
- * Category 2 (K2) equipment: For use in harsh environments with high mechanical, physical and chemical impact

Schlagworte:

Subtitle:

The work spotlights with clamping device can be attached anywhere and optimally aligned for the work application thanks to the ball joint.

Print-Beschreibung:

- * Ideally suited for assembly work, in cellars and on workbenches.
- * Work spotlight with special clamping device for easy mounting by clamping to work surfaces, pipes, panels, etc.
- * Lightweight and robust plastic housing with strong, sturdy clip.
- * Easy alignment of the working light thanks to ball bearing, the angle of inclination of the working light is flexibly adjustable.
- * With ball joint for individual alignment in all directions by almost 360 degrees.
- * Integrated USB power bank for charging smartphones etc.
- * Li-Ion battery 7.4V/5Ah with charging indicator.
- * Light duration up to 12h, charging time approx. 5h.
- * Category 2 (K2) equipment: Use for rough operation with high mechanical, physical and chemical effects.

Infotext:

Table article information:

Scope of supply:

Media



/publicpictures/Logo-Brennenstuhl/logo-engineered-in-germany.eps



/publicpictures/lcon/icon-norm-bgi-608-k2.eps



/publicpictures/lcon/icon-stossfest-ik08.eps



/publicpictures/lcon/icon-leuchtdauer-12h-max.eps



/publicpictures/lcon/icon-stecksystem-usb-powerbank.eps



/publicpictures/lcon/icon-schutzart-ip65.eps



/publicpictures/lcon/icon-lumen-3800.eps



/publicpictures/Detailansicht/1173070020-perspektive.tif



/publicpictures/Detailansicht/1173070020-frontansicht.tif



/publicpictures/Detailansicht/1173070020-seitenansicht.tif



/publicpictures/Detailansicht/1173070020-hinten.tif




/publicpictures/Detailansicht/1173070020-laden.tif



/publicpictures/Detailansicht/1173070020-klemmbuegel-stange.tif



/publicpictures/Anwendung/1173070020-anwendung-smartphone-laden.tif



/publicpictures/Anwendung/1173070020-anwendung-sicherungskasten-klemmbuegel-2.tif




/publicpictures/Anwendung/1173070020-anwendung-baustelle-sanitaer-klemmbuegel.tif



/publicpictures/Anwendung/1173070020-anwendung-baustelle-klemmbuegel-9.tif



/publicpictures/Anwendung/1173070020-anwendung-baustelle-klemmbuegel-6.tif



/publicpictures/Anwendung/1173070020-anwendung-baustelle-klemmbuegel-8.tif

/restrictedpictures/QR-Code/1173070020-qr-code-info.eps

Context

Attributkategorie:

Light

Accessories:

Garantie:

Other (legal)

Ersatzteil:

Similar products:

Technical data

Batterie

Degree of protection (IP):

IP65

Battery type:

Built-in battery pack

Suitable for outdoor area:

Yes

Battery technology:	Lithium-ion	Impact strength:	IK08
Rechargeable:	Yes	Shock resistance:	Yes
Number of cells:	4	Watertight:	No
Light duration:	12h	Min. operation temperature:	-10°C
Capacity:	5Ah	Max. operation temperature:	40°C
Voltage:	7.4V	Leuchte3Stecksystem	
IEC indication:	Other	With socket outlet:	No
Other indications:	Other	With usb output:	Yes
Einsatz im Ex-Bereich - ep:	No	Type of plug - Input:	USB
With battery charging indicator:	Yes	Load input:	Yes
With battery status indicator:	Yes	USB-Cable length:	1m
Backup battery included:	Without	Leuchte4Details	
Power:	37Wh	For "complicated conditions" (according to VDE):	Yes
Loading current:	2,000mA	Leuchtmittel0Allgemein	
Charging time:	5h	Lamp type:	LED non-replaceable
Dangerous goods regulations:	Yes	Leuchtmittel1Betriebseigenschaften	
Closed (sealed):	Yes	Life time of light:	54,000h
Leuchte0Allgemein		Colour rendering index CRI:	80-89 (class 1B)
Type of lamp:	Floodlight	Colour temperature:	6,400K
Model:	Other	Adjustable colour temperature:	No
Reflector:	Matt	Colour of light - ep:	864
Housing material:	Plastic/ metal	Fluorescent colour:	white
Surface:	Other	Multicolour- switch steps:	No
Surface finishing:	Matt	Adjustable luminous flux:	Levels
Halogen free:	Yes	Total luminous flux:	3,800lm
Housing colour:	black	Netzteil	
Colour cover:	white	externes Netzteil:	No
Colour:	black, grey	Optionales externes Netzteil verfügbar:	No
Lamp type included:	Yes	Output voltage:	5V
Number of lamps:	84	Nominal input voltage:	5V
Number of batteries:	1	Output current:	2A

Battery included:	Yes	With power supply:	No
Rotatable - ep:	Yes	With charge cable:	Yes
Collapsible/ Bendable:	Yes	Min. nominal voltage at charge cable:	5V
Colour controllable (RGB):	No	Mgv	
Packaging:		Packaging unit (UP):	1
Adjustable colour temperature:	No	Weight of product (without packaging):	1.63kg
Adjustable luminous flux:	Levels	Length of product (without packaging):	12.5cm
Luminous flux:	3,800lm	Width of product (without packaging):	16cm
Suitable for emergency lighting:	No	Height of product (without packaging):	25cm
Emergency unit integrated:	No	Weight of product (including packaging):	1.9kg
With orientation lighting:	No	Length of product (including packaging):	13.2cm
Suitable for accent lighting:	No	Width of product (including packaging):	16.7cm
Fit for monitor workplace:	No	Height of product (including packaging):	26.3cm
Multicolour- switch steps:	No		

Leuchte1elektrWerte

Protection class:	III
Power supply:	Rechargeable battery
Load input for external power supply:	Yes
Power consumption:	40W
Output voltage:	5V
Nominal input voltage:	5V
Type of output voltage:	Direct voltage (DC)
Type of input voltage:	Alternating voltage (AC)
Max. output current USB:	2A

Leuchte2Anwendung

With on/off switch:	Yes
With twilight switch:	No

Variantgroup

LED battery spotlight CL with clamping device

- * Ideally suited for assembly work, in cellars and on workbenches.
- * Work spotlight with special clamping device for easy mounting by clamping to work surfaces, pipes, panels, etc.
- * Lightweight and robust plastic housing with strong, sturdy clip.
- * Easy alignment of the working light thanks to ball bearing, the angle of inclination of the working light is flexibly adjustable.
- * With ball joint for individual alignment in all directions by almost 360 degrees.
- * Integrated USB power bank for charging smartphones etc.
- * Category 2 (K2) equipment: For use in harsh environments with high mechanical, physical and chemical impact.

Related Article

1173070010

1173070020

Variant Differentiation

Objektbrick Leuchtmittel1Betriebseigenschaften: Attribut max_luminous_flux