HT-SCE-1K-3/4-2.0-0 ACTIVE

HT-SCE

TE Internal #: 131854-000

HT-SCE, Printable Tubing, Ladder, High Temperature, 2:1 Shrink

Ratio, Black, Markers per Sleeve 1, Length 50.8 mm [2 in]

View on TE.com >



Identification & Labeling > Printable Tubing > HT-SCE HIGH TEMPERATURE SLEEVES



Printable Tubing Type: Ladder

Printable Tubing Grade: High Temperature

Printable Tubing Shrink Ratio: 2:1
Primary Product Color: Black

Markers per Sleeve: 1

All HT-SCE HIGH TEMPERATURE SLEEVES (66)

Features

Product Type Features

rioduct Type realures	
Printable Tubing Type	Ladder
Printable Tubing Grade	High Temperature
Body Features	
Printable Tubing Shrink Ratio	2:1
Primary Product Color	Black
Markers per Sleeve	1
Dimensions	
Product Length	50.8 mm[2 in]
Supplied Inner Diameter	19 mm[.75 in]
Recovered Inside Diameter	9.5 mm[.375 in]
Compatible Cable Diameter Range	9.9 – 15.3 mm[.39 – .602 in]
Usage Conditions	
Operating Temperature Range	-55 – 225 °C[-67 – 437 °F]
Operation/Application	

See TE Document 411-121005 the Printer

Product Ribbon Matrix

Recommended Ribbon



Printer/Label Features

Recommended Printer	See TE Document 411-121005 the Printer Product Ribbon Matrix
Printer Technology	Thermal Transfer
Packaging Features	
Packaging Quantity	1000

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2022 (223) Candidate List Declared Against: JUL 2021 (219) SVHC > Threshold: Not Yet Reviewed
Halogen Content	Low Bromine/Chlorine - Br and Cl < 900 ppm per homogenous material. Also BFR /CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts

HT-SCE, Printable Tubing, Ladder, High Temperature, 2:1 Shrink Ratio, Black, Markers per Sleeve 1, Length 50.8 mm [2 in]





TE Part # 1-2186502-1 T3224-PRINTER



TE Part # 1-2186503-1 T3224-SWARE-PRINTER



TE Part # 154739-000 T300-RIBBON-WH-4HT



TE Part # CP8122-000 T6112DS-PRINTER



TE Part # 1-2186500-1 T3212-PRINTER



TE Part # 1-2186501-1 T3212-SWARE-PRINTER

Also in the Series | HT-SCE





Printable Tubing(19)

Customers Also Bought



TE Part #A27893-000 HT-SCE HIGH TEMPERATURE SLEEVES



TE Part #ZPF000000000008984 983-6SE 22-19 PN-L



TE Part #YCTJ122E04FC015000 **ELEC MODULE**



TE Part #355207N001 RT-1145-OX-14-0-CS6302

TE Part #811085N003 222D163-12-0-CS6385 TE Part #ZPF000000000097356 768-0331-00 E

TE Part #241165N002 RT-1145-OX-22-0-CS6302 TE Part #455221N002 RT-1145-OX-32-0-CS6302 HT-SCE, Printable Tubing, Ladder, High Temperature, 2:1 Shrink Ratio, Black, Markers per Sleeve 1, Length 50.8 mm [2 in]



Documents

Product Drawings

HT-SCE-1K-3/4-2.0-0

English

Datasheets & Catalog Pages

HT-SCE Heat Shrinkable Sleeves

English

Product Specifications

Product Specification

English

IDENTIFCATION PRINTER PRODUCT RIBBON MATRIX

English

Instruction Sheets

Instruction Sheet (non U.S.)

English