

SENCITY® Rail MIMO Antenna 1399.17.0221

Description

Railway rooftop antenna for Cellular and Wi-Fi bands.
 Supports 2x2 Cellular MIMO for 3G, 4G and 5G.
 Supports 2x2 Wi-Fi MIMO in all Wi-Fi 6E bands.
 Rugged design, meets EN 50155 Railway Standard.
 Fire retardant according to EN 45545-2 and NFPA-130.
 Dedicated grounding contact (optional).
 Cable conduit support (optional).



Product Configuration

Technical Data

Electrical Data

| | Band 1 | Band 2 | Band 3 | Band 4 |
|--------------------------|--------------|--------------|--------------|--------------|
| Band Name | Cell/Wi-Fi 1 | Cell/Wi-Fi 2 | Cell/Wi-Fi 3 | Cell/Wi-Fi 4 |
| Frequency (MHz) | 617 - 694 | 694 - 790 | 790 - 960 | 1350 - 2700 |
| VSWR | 1.7 | 1.7 | 1.7 | 1.8 |
| Impedance (Ohm) | 50 | 50 | 50 | 50 |
| Gain (dBi) | 6 | 5 | 6 | 7.5 |
| Composite power max (W) | 250 | 180 | 130 | 130 |
| Ambient temperature (°C) | 25 | 25 | 25 | 25 |
| Port Isolation (dB) | 15 | 15 | 15 | 20 |

| | Band 5 | Band 6 | Band 7 |
|--------------------------|--------------|--------------|--------------|
| Band Name | Cell/Wi-Fi 5 | Cell/Wi-Fi 6 | Cell/Wi-Fi 6 |
| Frequency (MHz) | 2700 - 3300 | 3300 - 4900 | 4900 - 7125 |
| VSWR | 2 | 2.1 | 1.9 |
| Impedance (Ohm) | 50 | 50 | 50 |
| Gain (dBi) | 6.5 | 6.5 | 7.5 |
| Composite power max (W) | 100 | 100 | 100 |
| Ambient temperature (°C) | 25 | 25 | 25 |
| Port Isolation (dB) | 25 | 25 | 35 |

Ports

| | Port 1 | Port 2 |
|------------------|------------------|------------------|
| Port name | Cell/Wi-Fi 1 | Cell/Wi-Fi 2 |
| Connector | N, jack (female) | N, jack (female) |
| Cable Type | RADOX_RF_142 | RADOX_RF_142 |
| Cable Length (m) | 0.2 | 0.2 |
| Polarization | vertical | vertical |
| DC grounded | Yes | Yes |

Connections

| | Band 1 | Band 2 | Band 3 | Band 4 | Band 5 | Band 6 | Band 7 |
|--------|--------|--------|--------|--------|--------|--------|--------|
| Port 1 | X | X | X | X | X | X | X |
| Port 2 | X | X | X | X | X | X | X |

General Data

SENCITY® Rail MIMO Antenna 1399.17.0221

Indicated VSWR values are valid for a metallic ground plane of 0.5 x 0.5m or larger. In the 790-7125 MHz band, Indicated VSWR values are also valid for installations on non-metallic surfaces (no specific ground plane requirements). Indicated gain values will be achieved on a metallic ground plane of 1 x 1 m or larger.

There is no applicable EU directive nor related harmonized standard for passive antennas. Consequently there is no CE marking on these antennas and no EU Declaration of Conformity can be issued.

Mechanical Data

| | |
|-----------------|---|
| Dimensions (mm) | 81.6 x 102.5 x 352.5 (Height x Width x Depth) |
| Weight (kg) | 2 |

High-voltage-protection: no voltage on RF port, if the catenary line touches the antenna (EN 50124-1, 3.8 kVDC, 27.5 kVAC, 1min).

High-current-protection: Designed acc. to UIC 533, DC-grounded antenna element (protection against lightning and short circuit with catenary lines(40kA/0.125s, 70kA/0.05s).

Corrosion: Low corrosion design acc. to MIL-DTL-14072(E), 96 hours Salt Spray test.

Mounting: Shall be installed in longitudinal position to the wind/driving direction.

Suitable for installation on high speed trains with a maximum speed of 500 km/hr.

4x composite sealing washers included for silicone-free sealing of the mounting screws.

Environmental Data

| | |
|--|---------------------------|
| Environmental conditions | outdoor |
| Operation temperature (°C) | -55 to 85 |
| Storage temperature (°C) | -55 to 85 |
| Transport temperature (°C) | -55 to 85 |
| IP rating | IP67, IP69 |
| Flammability rating | EN 45545-2 R24 HL3 |
| Solar radiation | UL 746C, F1 |
| 2011/65/EU (RoHS - including 2015/863 and 2017/2102) | compliant acc. Annex III |
| Lead-free soldered | yes |
| WEEE 2012/19/EU | no special marking needed |
| ELV 2000/53/EC | compliant |
| REACH 1907/2006/EC | compliant |

Environmental tests: EN 50155:2018-05

Flammability rating: EN45545-2:2013 + A1:2015, NFPA-130:2017

Tested according to ISO 4589-2:2017, NFX 70-100-1:2006, ISO 5659-2:2011.

Material Data

| | |
|--------------------------------|----------------------|
| Radome colour | RAL 7043 (dark grey) |
| Radome material | PC (Polycarbonate) |
| Back plate/base plate colour | grey |
| Back plate/base plate material | Aluminium |
| Plating | Passivated (Plating) |

Related Products

9091.99.0235 Sencity Rail Antenna grounding kit

9091.99.0236 Sencity Rail conduit Support Kit

9091.99.0256 Sencity Rail - M8 sealing washer kit

9091.99.0261 Sencity Rail antenna mounting plate

Related Documents

| | |
|----------------------|----------------|
| Mounting instruction | DOC-0000443802 |
| Painting instruction | DOC-0000256180 |
| Security instruction | DOC-0000278984 |
| Outline drawing | DOU-00341713 |
| 3D-model | DOC-0000786471 |

Additional Information

This product meets the Deutsche Bahn specifications for rolling stock equipment. Protected by Patents: DE202015009331(U1), US10116056(B2), CN106663861B.

SENCITY® Rail MIMO Antenna 1399.17.0221