

## SENCITY® Omni-S Thimble 1399.17.0224

### Description

Broadband omnidirectional WiFi & Cellular antenna from 1710 MHz up to 7125 MHz  
 WiFi-4, WiFi-5, WiFi-6, WiFi-6E  
 4G and 5G frequencies band  
 Small & robust outdoor stick antenna IP66 / IP68 / IP69K  
 Direct mount on N type connector of wireless access points or clients



### Product Configuration

### Technical Data

#### Electrical Data

	Band 1	Band 2	Band 3	Band 4
Frequency (MHz)	1710 - 2000	2000 - 2700	2700 - 4200	4900 - 5150
VSWR	2	2	2	2
Impedance (Ohm)	50	50	50	50
Gain (dBi)	1.5	2	1.5	2.5
3dB beamwidth (h) (°)	360	360	360	360
Composite power max (W)	200	160	120	120
Ambient temperature (°C)	25	25	25	25

  

	Band 5	Band 6
Frequency (MHz)	5150 - 5925	5925 - 7125
VSWR	2	2
Impedance (Ohm)	50	50
Gain (dBi)	2.5	3
3dB beamwidth (h) (°)	360	360
Composite power max (W)	120	120
Ambient temperature (°C)	25	25

#### Ports

	Port 1
Connector	N, plug (male)
Polarization	vertical
DC grounded	No

#### General Data

#### Mechanical Data

Dimensions (mm) 55 x 22 (Height x Diameter)  
 Weight (kg) 0.05

Coupling nut torque: nominal 1Nm  
 maximum 3Nm

#### Environmental Data

Environmental conditions outdoor  
 Operation temperature (°C) -40 to 85  
 Storage temperature (°C) -40 to 85  
 Transport temperature (°C) -40 to 85  
 IP rating IP66, IP68  
 Flammability rating UL 94-HB  
 2011/65/EU (RoHS - including 2015/863 and 2017/2102) compliant  
 Lead-free soldered not soldered  
 WEEE 2012/19/EU special marking needed  
 REACH 1907/2006/EC compliant

## SENCITY® Omni-S Thimble 1399.17.0224

Ingress protection IP66, IP68 & IP69K (EN 60529)

Flammability rating EN 45545 DIN 5510-2

Temperature range (damp heat) EN 60068-2-30, Test Db, Variant 1 (40°C 6 cycles)

Temperature shock EN 60068-2-14, Test N, -45°C/85°C, 1h, 5 cycles

Vibration and shock EN 61373, category 1, class b (for railway carriage)

### Material Data

Radome colour	RAL 7043 (dark grey)
Radome material	ASA (acrylic ester-styrene-acrylonitrile)

### Related Documents

Painting instruction	DOC-0000256180
Security instruction	DOC-0000278984
Outline drawing	DOU-00248614
3D-model	DOC-0000424893