

Power connectors - CUC-PPC-C2ZNI-SS/24FKP5 - 1421785

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Power connectors, degree of protection: IP65/67, number of positions: 5, material: Zinc die-cast, connection cross section: AWG 18- 13, cable outlet: straight

Your advantages

- Fixed coding
- Increased temperature range
- Lockable
- One-part housing



Key Commercial Data

Packing unit	1
GTIN	 4 055626 299792
GTIN	4055626299792
Custom tariff number	85366990

Technical data

Dimensions

External cable diameter	6.5 mm ... 9 mm
Type	fixed coding

Ambient conditions

Degree of protection	IP65/IP67
Ambient temperature (operation)	-40 °C ... 85 °C
Ambient temperature (assembly)	-10 °C ... 40 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C

General data

Note	This product corresponds to the PROFINET Cabling and Interconnection Technology Guideline for PROFINET regulations, version 2.00, order no: 2.252, Chapter 11 Connectors for 24 Volt Power Supply Cabling and
------	---

Power connectors - CUC-PPC-C2ZNI-SS/24FKP5 - 1421785

Technical data

General data

	Chapter 13 Application specific Cabling and Interconnection Technology (AIDA)
Rated current at 40°C	16 A
Rated voltage	24 V
Number of positions	5
Degree of pollution	3
Alternative short product description	MSTB connector
Locking type	Push Pull
Rated voltage (II/2)	630 V
Rated voltage (III/2)	400 V
Rated voltage	250 V
Rated surge voltage (II/2)	4 kV
Rated surge voltage (III/2)	4 kV
Rated surge voltage (III/3)	4 kV
Rated current	16 A
Rated voltage (III/3)	24 V
Conductor cross section	0.75 mm ² ... 2.5 mm ²
Connection cross section AWG	18 ... 13
COMBICON connection data	0.75 mm ² 2.5 mm ² 0.75 mm ² 2.5 mm ² 18 13 2.5 mm ²
Conductor cross section flexible, with ferrule without plastic sleeve min.	0.75 mm ²
Conductor cross section flexible, with ferrule without plastic sleeve max.	2.5 mm ²
Conductor cross section flexible, with ferrule with plastic sleeve min.	0.75 mm ²
Conductor cross section flexible, with ferrule with plastic sleeve max.	2.5 mm ²
Contact material	Copper alloy
Contact carrier material	PA
Contact surface material	Gold over nickel
Housing material	Zinc die-cast

Characteristics head 1

Stripping length of the individual wire	10 mm
Stripping length of the sheath	40 mm

Standards and Regulations

Flammability rating according to UL 94	V0
--	----


Environmental Product Compliance

China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Drawings


Power connectors - CUC-PPC-C2ZNI-SS/24FKP5 - 1421785

Schematic diagram



Pin assignment PROFINET push-pull, power connector, 24 V, fixed coding

Dimensional drawing



Push/pull connector

Classifications

eCl@ss

eCl@ss 4.0	272607xx
eCl@ss 4.1	27260701
eCl@ss 5.0	27143424
eCl@ss 5.1	27260700
eCl@ss 6.0	27260700
eCl@ss 7.0	27440101
eCl@ss 8.0	27440101
eCl@ss 9.0	27440101

ETIM

ETIM 2.0	EC000438
ETIM 3.0	EC000438
ETIM 4.0	EC000438
ETIM 5.0	EC002636
ETIM 6.0	EC002636

UNSPSC

UNSPSC 6.01	30211923
UNSPSC 7.0901	39121522
UNSPSC 11	39121522
UNSPSC 12.01	39121522
UNSPSC 13.2	39121409

Approvals

Approvals

Approvals

cULus Recognized / EAC

Power connectors - CUC-PPC-C2ZNI-SS/24FKP5 - 1421785

Approvals

Ex Approvals

Approval details

cULus Recognized		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm E118976-20080903
Nominal voltage UN	24 V	
Nominal current IN	16 A	
mm ² /AWG/kcmil	14	

EAC		B.01742
-----	--	---------

Accessories

Accessories

Connector

Ferrule - AI 1,5 -10 BK - 3200195



Ferrule, sleeve length: 10 mm, length: 16 mm, color: black

Ferrule - AI 2,5 -10 BU - 3202533



Ferrule, sleeve length: 10 mm, length: 17 mm, color: blue

Data cable by the meter

Power connectors - CUC-PPC-C2ZNI-SS/24FKP5 - 1421785

Accessories

Power cable - VS-PN-CABLE-1021/PVC-5X1,5/100 - 1659007



Power cable, cable length: 100 m, number of positions: 5

Tool - CRIMPFOX ZA 3 - 1201882



Crimping pliers, for ferrules in accordance with DIN 46228-1: 1992-08 and DIN 46228-4: 1990-09

Power cable - VS-PN-CABLE-1021/PVC-5X1,5/... - 1658998



PROFINET power cable, 5x 1.5 mm², stranded (7-wire), outer sheath: PVC, outside diameter 10 mm, RAL 7001 (silver gray), oil-resistant, by the meter

Additional products

Panel mounting frames - VS-PPC-F2-MSTB-MNNA-1R-P - 1608087



MSTB panel mounting frame, IP67, for push-pull interlocking, metal, for PCB connection, for square panel cutout, with grommet, without mounting screws

Panel feed-through - CUC-V14-F2ZNI-EM/24FN5:FC - 1408235



Push/pull panel mounting frame, metal, version 14, including contact insert with spring-cage connection, flexible coding, for rectangular mounting cutout, with seal, without fixing screws

Power connectors - CUC-PPC-C2ZNI-SS/24FKP5 - 1421785

Accessories

Panel mounting frames - CUC-V14-F2ZNI-SC/24FN5:FC - 1409036



MSTB panel mounting frame, IP67, for push-pull interlocking, metal, with integrated contact insert for conductor connection, spring-cage connection, 24 V, for round mounting cutout, with seal, without mounting screws

Female insert - VS-MSTBAH 2,5/ 5-GB-5,08-BK-A - 1657915



MSTB contact insert, for PCB assembly, 24 V, 5-pos., with angled solder pins, RAL 9005 (black), for panel mounting frame VS-PPC-F2-MSTB-...-1R-P

Female insert - VS-MSTBVA 2,5/ 5-GB-5,08-BK-A - 1609565



MSTB contact insert, for PCB assembly, 24 V, 5-pos., with straight solder pins, RAL 9005 (black), for panel mounting frame VS-PPC-F2-MSTB-...-1R-P

Protective cap - VS-PPC-F2-PC-POBK - 1405329



Protective cap, IP65, with push-pull locking for covering the contact insert in the push-pull connector for Power, plastic

Power distributor - VS-PPC-J-4X-1227 - 1405387



Power H distributor, 4 x MSTB contact inserts, metal housing, without mounting screws

Power connectors - CUC-PPC-C2ZNI-SS/24FKP5 - 1421785

Accessories

Y distributor - VS-PPC-J-1220-1227-1020-... - 1405484



PROFINET Y distributor with assembled power line, 5-pos., IP65/IP67, MSTB plug with metal housing on 2x socket in metal housing, variable cable length

Power cable - VS-PN-CABLE-1021/PVC-5X1,5/100 - 1659007



Power cable, cable length: 100 m, number of positions: 5

Power cable - VS-PN-CABLE-1021/PVC-5X1,5/... - 1658998



PROFINET power cable, 5x 1.5 mm², stranded (7-wire), outer sheath: PVC, outside diameter 10 mm, RAL 7001 (silver gray), oil-resistant, by the meter