

LED Floodlight RGBW Basic 50W + Remote

Bailey nr.: 143756



BAI LED Floodlight RGBW Basic 50W + Remote Cool white 1000lm Red 125lm Green 720lm Blue 230lm IP65 IK05 120D 220-240V Cable 0.5m BaiColour

Basic LED RGBW floodlight for decorative lighting. With the remote control, many colors and also white light can be set. In addition to red 660-670nm, green 520-530nm and blue 450-460nm, there are 3 other pre-programmed colors to select. With memory function. In addition, there are 2 automatic color change programs and you can adjust the brightness. The range of the RF remote control is 8-10m. Ambient temperature: -20°C to + 45°C.

General properties	
EAN-code	8714681437568
Product series	LED Floodlight BaiColour
Product Type	RGBW Basic
Specifications	
Adjustability	Swivelling
With movement sensor	No
With light sensor	No
With light source	Yes
Lamp holder	None
Material housing	Aluminium
Surface protection	Powder coating
Colour housing	Black
Material cover	Glass transparent
Nominal voltage (V)	220 240 V
Voltage type	AC
LED nominal current at constant current	100 120 mA
Dimmable	Yes
Light sharing	Symmetric
Beamangle	Extreme wide beam >80°
Rated life time L70/B10 at 25 °C	
Rated life time L70/B50 at 25 °C	25000 h
Rated life time L80/B10 at 25 °C	
Rated life time L80/B50 at 25 °C	
Rated life time L90/B10 at 25 °C	
Rated life time L90/B50 at 25 °C	
Degree of protection (IP)	IP65
Impact strength	IK05
Protection class	I
Rated ambient temperature	-20 45 °C
Max. system power (W)	50 W
Colour of light	RGBW
Colour temperature (K)	
Colour rendering index CRI	70-79

Specifications	
Luminous flux (lm)	125 1000 lm
Lamp efficacy (lm/w)	21 lm/W
Power factor	0.9
Width	215 mm
Height/depth	23 mm
Length	195 mm
Outer diameter	
Built-in height/depth	
Built-in diameter	

Bailey 143756

This luminaire contains built-in LED lamps.

The lamps cannot be changed in the luminaire.

874/2012