

battery type: Alkaline Manganese (Mercury free)
battery size: IEC: LR14; JIS: AM-2; ANSI: C; MN1400; Baby
chemical system: Zn / KOH-H₂O / MnO₂

nominal voltage: 1.5 V
open circuit voltage: 1.57...1.62 V new battery
 1.55...1.62 V after 1 year storage at 20°C

capacity rated: 7200 mAh all measurements at 20°C ambient
 discharge at 25mA load; 24h/day
 End Voltage (EV): 0.8V
 6800 mAh discharge at 20ohms load; 24h/day
 End Voltage (EV): 0.9V

minimum: 5800 mAh discharge at 75mA constant current
 End Voltage (EV): 0.8V
 2250 mAh discharge at 1000mA constant current
 End Voltage (EV): 0.8V

typical service output (new batteries)

- ≥ 18 h load resistor 3.9ohms; EV: 0.9V
discharge 4min/h 8h/d
- ≥ 18 h load resistor: 3.9ohms; EV: 0.8V
discharge 1h/d
- ≥ 31 h load resistor: 6.8ohms; EV: 0.9V
discharge 1h/d
- ≥ 16 h load resistor: 3.9ohms; EV: 0.9V
discharge 24h/d
- ≥ 100 h load resistor: 20ohms; EV: 0.9V
discharge 4h/d

internal resistance: ≤ 0.2 Ω at 1kHz, sine wave measurement
according to IEC 896-2

shelf life: 7 years under proper storage conditions


leakage resistance
 over discharge: no leakage 3.9ohms continuous discharge for 48h; ta: 20°C; RH: 60±15%
 high temperature: no leakage store 20days at ta: 60°C; RH:90±5%

ambient temperature range: - 10...50 °C


recommended storage conditions: 5...25 °C ambient temperature
 45...75 % rel. humidity

mechanical specifications

cell dimensions
 diameter d1: 26.0 - 1.0 mm
 diameter d2: 7.0 - 1.0 mm
 height h1: 50.0 - 1.0 mm
 height h2: 2.0 - 0.4 mm
 weight: 70 ± 3 g



blister package:
 dimensions: 120 x 85 mm
 weight (incl. batteries): 148 ± 10 g

	ANSMANN Specifications for model:	Ansmann RED Alkaline battery
		C - size
		2pcs blister
	data sheet no. / part no.	1513-0000
	supplier no.	703385
	author / date	TG / 11.01.2017