

**Industrial Ethernet  
IE-FCI-PWB-RCBO**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 1429-0  
 Fax: +49 5231 14292083  
 www.weidmueller.com



FrontCom® Vario integrates multiple functions in only one single frame. The system is easy to install and you can select from a wide range of data, signal and power modules. In addition to being extremely compact, FrontCom® Vario offers a number of unique product features that will make your project planning and work activities secure, fast and future-proof. Furthermore, the FrontCom® Vario system has an attractive housing design that, by the way, offers highest impact-resistance and fully meets the requirements of IP 65 protection class.

**General ordering data**

Type	IE-FCI-PWB-RCBO
Order No.	<a href="#">1534250000</a>
Version	FrontCom, Insert Power large, RCBO
GTIN (EAN)	4050118337938
Qty.	1 pc(s).

**Industrial Ethernet  
IE-FCI-PWB-RCBO**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 1429-0  
 Fax: +49 5231 14292083  
 www.weidmueller.com

**Technical data**

**Dimensions and weights**

Net weight 74 g

**Temperatures**

Operating temperature -5 °C...40 °C Storage temperature  
 Installation temperature

**General data**

Insert type Insert Power large Protection degree IP20

**Clampable conductors**

Conductor connection cross-section, extremely flexible with wire end ferrule	1.5 ... 2.5 mm <sup>2</sup>	Conductor connection cross-section, flexible with wire end ferrule	1.5 ... 2.5 mm <sup>2</sup>
Conductor connection cross-section, rigid	1.5 ... 2.5 mm <sup>2</sup>	Type of connection	Screw connection

**Standards**

Certificate No. (GERMLLOYD) 13866-15

**Technical data**

Type of connection	Screw connection	Triggering characteristic	Typ C
Operating voltage	230 V AC	Rated current	16 A
IΔn	30 mA	IΔm	500 A

**Downloads**

GL Approval Guidelines GL\_FrontCom.pdf

**Classifications**

ETIM 5.0	EC000456	ETIM 6.0	EC001121
UNSPSC	31-16-23-03	eClass 6.2	27-26-12-90
eClass 7.1	27-18-92-17	eClass 8.1	27-18-92-17
eClass 9.0	27-18-92-17	eClass 9.1	27-18-90-90

**Approvals**

Approvals



**Industrial Ethernet  
IE-FCI-PWB-RCBO**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 1429-0  
Fax: +49 5231 14292083  
[www.weidmueller.com](http://www.weidmueller.com)

**Drawings**

**Triggering characteristic**

