

Alcoswitch

TE Internal #: 1571294-2

Tactile Switches, Round Actuator Style, Yes, Stainless Steel, Silver,

Dust Proof, Low Profile, 50 mA, 24 VDC, Process Sealed

View on TE.com >



Relays, Contactors & Switches > Switches > Tactile Switches



Actuator Style: Round
Operating Function: Yes

Contact Base Material: Stainless Steel
Switch Contact Plating Material: Silver

Dust Proof: Yes

Features

Product Type Features

Product Type	Switch
Leg Style	Gull Wing
Illuminated	With
Actuator Style	Round
Dust Proof	Yes

Configuration Features

Tactile Feel	With
ESD Grounding Terminal	Without
Ganged	With
Tactile	Yes
Snap Action	Without
Operating Function	Yes
Support Bracket	Without
Configuration (Pole-Throw)	Single Pole - Single Throw
Number of Actuators	1

Electrical Characteristics

Tactile Switch Voltage Rating	24 VDC
-------------------------------	--------

Body Features

Cover Material Nickel Silver Alloy



Case Color	Black
Actuator Force	160 g[5.648 oz]
Case Material	Thermoplastic (LCP)
Bushing Style	Unthreaded
Actuator Profile	Extended
Actuator Material	Thermoplastic
Actuator Color	Black
Contact Features	
Contact Base Material	Stainless Steel
Switch Contact Plating Material	Silver
Tactile Switch Contact Current Rating	50 mA
Termination Features	
Termination Type	Printed Circuit Board
Mechanical Attachment	
Tactile Switch Mounting Type	Surface Mount
Tactile Switch Mounting Angle	With
Housing Features	
Low Profile	With
Process Sealed	Yes
Dimensions	
Actuator Length	1.9 mm[.074 in]
Button Width	3.09 mm[.122 in]
Switch Height	4.3 mm[.169 in]
Usage Conditions	
Temperature Rating	Standard °C
Packaging Features	
Packaging Method	Tape & Reel
Other	
Comment	(On) indicates momentary position.

Product Compliance

For compliance documentation, visit the product page on TE.com>



EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Not Yet Reviewed
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2022 (223) Candidate List Declared Against: JUL 2021 (219) SVHC > Threshold: Not Yet Reviewed
Halogen Content	Not Yet Reviewed for halogen content
Solder Process Capability	Reflow solder capable to 260°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

TE Part # 4-1437565-2

FSM4JSMATR=TACT SWITCH 6X6MIL

TE Part # 3-1437565-0

FSM2JSMATR=ON T/R

Compatible Parts



Customers Also Bought





















Documents

Product Drawings

SWITCH,TACT,SMT,SEALED,T&R

English

CAD Files

Customer View Model

ENG_CVM_CVM_1571294-2_G.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1571294-2_G.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1571294-2_G.3d_stp.zip

English

By downloading the CAD file I accept and agree to the Terms and Conditions of use.

Datasheets & Catalog Pages

Tactile Switches, Round Actuator Style, Yes, Stainless Steel, Silver, Dust Proof, Low Profile, 50 mA, 24 VDC, Process Sealed



SWITCHES_CORE_PROGRAM_CATALOG

English

Products for Mobile Equipment

English