

**VPMS (blanking plug in brass)  
VP M32-MS65**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com



For sealing surplus threaded holes to maintain the IP class of protection

**General ordering data**

Type	VP M32-MS65
Order No.	<a href="#">177760000</a>
Version	VPMS (blanking plug in brass), Blanking plug, M 32, 8 mm, Brass, nickel-plated
GTIN (EAN)	4032248158034
Qty.	50 pc(s).

## Data sheet

### VPMS (blanking plug in brass) VP M32-MS65

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

## Technical data

### Dimensions and weights

Length	12 mm	Length (inches)	0.472 inch
Height	12 mm	Height (inches)	0.472 inch
Net weight	25.2 g	Diameter	35 mm

### Environmental Product Compliance

REACH SVHC Lead 7439-92-1

### General information

Material	Brass, nickel-plated	Cable glands	metric
External thread	M 32	Pitch of thread	1.5 mm
Length of thread	8 mm	Protection degree	IP68, IP68 - 5 bar (30 min.)
Operating temperature range, min.	-40 °C	Operating temperature range, max.	100 °C
Head diameter	35 mm	Halogen	No
O-Ring	NBR	Sealing	NBR

### Classifications

ETIM 6.0	EC000451	ETIM 7.0	EC000451
eClass 9.0	27-14-44-25	eClass 9.1	27-14-44-33
eClass 10.0	27-14-44-25	UNSPSC	30-21-18-01

### Approvals

Approvals



ROHS Conform

### Downloads

Brochure/Catalogue	<a href="#">CAT 3 HDC 17/18 EN</a> <a href="#">CAT 5 ENCL 17/18 EN</a>
Engineering Data	<a href="#">EPLAN, WSCAD</a>
Engineering Data	<a href="#">STEP</a>

**Data sheet**

**VPMS (blanking plug in brass)  
VP M32-MS65**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
[www.weidmueller.com](http://www.weidmueller.com)

**Drawings**

