

## Key Features:

- 22 Watt high performance fan
- Convenient, space saving bench top style
- East to replace activated carbon filter
- Economically and efficiently removes noxious fumes
- Full metal design with ground jack and 3 wire plug
- ESD Safe
- Air Flow: CFM 95/115

**Activated-Carbon Filter:** Size 130 x 130 x 10 mm (5.1 x 5.1 x 0.4 in.) Amount of Activated-Carbon filter 12g (0.03 lb.) Max. Absorbing weight of noxious components per filter 4 g (0.01 lb.) The filter is made by joining specific foam with refined activated carbon. The dust collection efficiency of the filter is 30% while the carbon filter can absorb up to 30% of its carbon weight in noxious components.

Replacement Filter for XY-426DLX:  
XY-76-3313010



### Ships with:

- Fume Extractor
- Power cord
- Filter
- Operation Manual

## 426DLX Bench Top Fume Extractor

*No More tears! Increased productivity! Improved work environment!...all by removing noxious fumes...*



### Product Description:

Convenient space saving fume extractor. Safely remove noxious fumes from your work environment, reducing headaches, nausea and eye irritations associated with the exposure to solder fumes. Removable cover enables multiple positions for efficient air ventilation, keep the cover on for up flow ventilation or remove for rear facing ventilation.

### 426 DLX Fume Extractor Specifications:

Input power	As requested
Wattage	20-22W
Max. air volume	95/115 CFM
Outer dimensions (W x H x D)	162 x 200 x 120 mm (6.38 x 7.78 x 4.72 in)
Weight (Including AC cord)	1600 grams (3.5 lbs.)
Filter size	130 m <sup>2</sup>
Filter weight	12 grams