

ERSADUR long-life soldering tip series 612



- CPS 60.10
- DIGITAL 60 A
- DIGITAL 2000 A with TECH TOOL soldering iron
- MICRO-CON 60 iA with TECH TOOL soldering iron

<p>0612SDLF</p> <p>pencil point, 0.4 mm \varnothing</p>	<p>0612UDLF</p> <p>pencil point, 0.8 mm \varnothing</p>	<p>0612BDLF</p> <p>pencil point, 1.0 mm \varnothing</p>	<p>0612CDLF</p> <p>chisel-shaped, 1.0 mm</p>
<p>0612ADLF</p> <p>chisel-shaped, 1.6 mm</p>	<p>0612KDLF</p> <p>chisel-shaped, 2.4 mm, bent</p>	<p>0612EDLF</p> <p>chisel-shaped, 3.2 mm \varnothing</p>	<p>0612GDLF</p> <p>pencil point, 1.6 mm \varnothing</p>
<p>0612JD</p> <p>chisel-shaped, 1.6 mm, bent 30°</p>	<p>0612ID</p> <p>pencil point, 0.4 mm \varnothing, bent 30°</p>	<p>0612MD</p> <p>PLCC blade, 1.5 mm</p>	<p>0612TW</p> <p>Ersa TechWell with concave portion, 3.0 mm</p>
<p>0612HD</p> <p>Ersa SolderWell with concave portion 2.5 mm, 30° bent</p>	<p>0612ZD</p> <p>WickTip, 10.5 x 3.6 mm</p>	<p>0612ND</p> <p>angled face, 3.0 mm, 45°</p>	<p>0612FDLF</p> <p>angled face, 2.0 mm, 45°</p>
<p>0612WDLF</p> <p>angled face, 4.0 mm, 45°</p>			

Desoldering tip series 662



- ELS 8000/M/D
- ELS 8100
- MS 8100D

<p>0662AE</p> <p>ERSADUR, 1.2 mm \varnothing (for joints with medium heat requirements)</p>	<p>0662BE</p> <p>ERSADUR, 1.0 mm \varnothing (for joints with medium heat requirements)</p>	<p>0662CE</p> <p>ERSADUR, 0.8 mm \varnothing (for joints with medium heat requirements)</p>
---	---	---