

**P-series  
PAP PDK 2.5/4**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com



Mounting plates that also act as end plates in the P-Series must be positioned every 200 mm when using the 10 x 3 busbar.

**General ordering data**

Type	PAP PDK 2.5/4
Order No.	<a href="#">1919720000</a>
Version	P-series, End plate, Dark Beige, 2.5 mm
GTIN (EAN)	4032248556236
Qty.	20 pc(s).

**Data sheet**

**P-series  
PAP PDK 2.5/4**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**Technical data**

**Dimensions and weights**

Width	2.5 mm	Height	80.75 mm
Depth	49.9 mm	Net weight	4.25 g

**Temperatures**

Continuous operating temp., min.	-50 °C	Continuous operating temp., max.	120 °C
----------------------------------	--------	----------------------------------	--------

**Additional technical data**

Installation advice	Direct mounting	Type of mounting	Direct mounting
Version	End plate		

**Material data**

Material	Wemid	Colour	Dark Beige
UL 94 flammability rating	V-0		

**System specifications**

Product family	P-series	Mounting rail	none
----------------	----------	---------------	------

**Classifications**

ETIM 3.0	EC000886	ETIM 4.0	EC000886
ETIM 5.0	EC000886	ETIM 6.0	EC000886
UNSPSC	30-21-18-27	eClass 5.1	27-14-11-33
eClass 6.2	27-14-11-33	eClass 7.1	27-14-11-33
eClass 8.1	27141133	eClass 9.0	27141133

**Approvals**

Approvals



ROHS	Conform
------	---------