

**VG Exe 7J (Ex plastic cable gland 7J Exe)
VG M32 EXE 16-21 SI 7J**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com



Polyamide cable glands, which are suitable for usage in explosion risk zones Ex e (increased safety) and Ex i (intrinsic safety).

On account of the enhanced EN60079-0:2009 testing requirements, there is now a version update of the standard (EN60079-0:2012) available.

Weidmüller offers a product family without restrictions and besides compliance with standards, the cable gland excels thanks to its increased impact resistance of 7 Joule and a possible temperature range down to -60°C without restrictions.

They have been tested to the current standard and EN 60079-0:2012 directive, and besides EAC, they are ATEX and IECEx certified.

General ordering data

Type	VG M32 EXE 16-21 SI 7J
Order No.	2017560000
Version	VG Exe 7J (Ex plastic cable gland 7J Exe), Cable glands, M 32, 10 mm, OD min. 16 - OD max. 21 mm, IP54, IP66, IP67, IP68 - 5 bar (30 min.), Polyamide 6
GTIN (EAN)	4050118400694
Qty.	25 pc(s).

**VG Exe 7J (Ex plastic cable gland 7J Exe)
VG M32 EXE 16-21 SI 7J**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Technical data
Dimensions and weights

Length	42 mm	Length (inches)	1.654 inch
Height	42 mm	Height (inches)	1.654 inch
Net weight	25.84 g		

General information

Material	Polyamide 6	External thread	M 32
Pitch of thread	1.5 mm	Length of thread	10 mm
AF size 1	36 mm	AF size 2	36 mm
Impact resistance	7 joules in acc. with IEC 60079-0	Protection degree	IP54, IP66, IP67, IP68 - 5 bar (30 min.)
Protection degree with GWDR	IP54, IP66, IP67, IP68 - 5 bar (30 min.)	Operating temperature range, min.	-60 °C
Operating temperature range, max.	70 °C	Outer cable diameter, min.	16 mm
Outer cable diameter, max.	21 mm	UL 94 flammability rating	HB
Seal insert	Silicone	Sealing	Silicone
Tightening torque	6 Nm	Torque for cap nut, min.	5 Nm
Torque for cap nut, max.	7 Nm	Torque for connecting adapter, min.	5 Nm
Torque for connecting adapter, max.	7 Nm	Torque for lock nut, min.	5 Nm
Torque for lock nut, max.	7 Nm	Explosion protection type	Improved safety Ex e
Standards	IEC 60079-0, EN 60079-0, IEC 60079-7, EN 60079-7, EN 60079-31, IEC 60079-31	Installation guidelines	See assembly instructions

Classifications

ETIM 6.0	EC000441	ETIM 7.0	EC000441
eClass 9.0	27-14-44-32	eClass 9.1	27-14-44-34
eClass 10.0	27-14-44-32		

Approvals

Approvals	CE; EAC; ATEX; IECEX; INMETRO
ROHS	Conform

Downloads

Brochure/Catalogue	CAT 5 ENCL 17/18 EN
Engineering Data	EPLAN, WSCAD
Engineering Data	STEP