

**VG Exi 7J (Ex plastic cable gland 7J Exi)  
VG M32 EXI 19-25 CR 7J**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com



Polyamide cable glands, which are suitable for usage in explosion risk zones Ex e (increased safety) and Ex i (intrinsic safety).

On account of the enhanced EN60079-0:2009 testing requirements, there is now a version update of the standard (EN60079-0:2012) available.

Weidmüller offers a product family without restrictions and besides compliance with standards, the cable gland excels thanks to its increased impact resistance of 7 Joule and a possible temperature range down to -60°C without restrictions.

They have been tested to the current standard and EN 60079-0:2012 directive, and besides EAC, they are ATEX and IECEx certified.

**General ordering data**

Type	VG M32 EXI 19-25 CR 7J
Order No.	<a href="#">2017760000</a>
Version	VG Exi 7J (Ex plastic cable gland 7J Exi), Cable glands, M 32, 15 mm, OD min. 19 - OD max. 25 mm, IP54, IP66, IP67, IP68 - 5 bar (30 min.), Polyamide 6
GTIN (EAN)	4050118400960
Qty.	20 pc(s).

**VG Exi 7J (Ex plastic cable gland 7J Exi)  
VG M32 EXI 19-25 CR 7J**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

**Technical data**
**Dimensions and weights**

Length	40.5 mm	Length (inches)	1.594 inch
Height	40.5 mm	Height (inches)	1.594 inch
Net weight	30 g		

**General information**

Material	Polyamide 6	External thread	M 32
Pitch of thread	1.5 mm	Length of thread	15 mm
AF size 1	42 mm	AF size 2	42 mm
Impact resistance	7 joules in acc. with IEC 60079-0	Protection degree	IP54, IP66, IP67, IP68 - 5 bar (30 min.)
Protection degree with GWDR	IP54, IP66, IP67, IP68 - 5 bar (30 min.)	Operating temperature range, min.	-40 °C
Operating temperature range, max.	70 °C	Outer cable diameter, min.	19 mm
Outer cable diameter, max.	25 mm	UL 94 flammability rating	HB
Seal insert	CR	Sealing	CR
Tightening torque	9 Nm	Torque for cap nut, min.	8 Nm
Torque for cap nut, max.	10 Nm	Torque for connecting adapter, min.	8 Nm
Torque for connecting adapter, max.	10 Nm	Torque for lock nut, min.	8 Nm
Torque for lock nut, max.	10 Nm	Explosion protection type	Intrinsically safe Ex i
Standards	IEC 60079-0, EN 60079-0, IEC 60079-7, EN 60079-7, EN 60079-31, IEC 60079-31	Installation guidelines	See assembly instructions

**Classifications**

ETIM 6.0	EC000441	ETIM 7.0	EC000441
eClass 9.0	27-14-44-32	eClass 9.1	27-14-44-34
eClass 10.0	27-14-44-32		

**Approvals**

Approvals	CE; EAC; ATEX; IECEX; INMETRO
ROHS	Conform

**Downloads**

Brochure/Catalogue	<a href="#">CAT 5 ENCL 17/18 EN</a>
Engineering Data	<a href="#">EPLAN, WSCAD</a>
Engineering Data	<a href="#">STEP</a>