

**VPK EX 7J (Ex blanking plug, plastic, 7J)  
VP M32 EX SI 7J**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

**Similar to illustration**



For sealing surplus threaded holes to maintain the IP class of protection

**General ordering data**

Type	VP M32 EX SI 7J
Order No.	<a href="#">2066750000</a>
Version	VPK EX 7J (Ex blanking plug, plastic, 7J), Blanking plug, M 32, 15 mm, IP54, IP66, IP67, IP68 - 5 bar (30 min.), Polyamide 6
GTIN (EAN)	4050118415445
Qty.	100 pc(s).

**VPK EX 7J (Ex blanking plug, plastic, 7J)  
VP M32 EX SI 7J**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**Technical data****Dimensions and weights**

Length	22.8 mm	Length (inches)	0.898 inch
Height	22.8 mm	Height (inches)	0.898 inch
Net weight	12.09 g		

**General information**

Material	Polyamide 6	External thread	M 32
Pitch of thread	1.5 mm	Length of thread	15 mm
AF size 1	36 mm	AF size 2	36 mm
Impact resistance	7 joules in acc. with IEC 60079-0	Protection degree	IP54, IP66, IP67, IP68 - 5 bar (30 min.)
Protection degree with GWDR	IP54, IP66, IP67, IP68 - 5 bar (30 min.)	Operating temperature range, min.	-60 °C
Operating temperature range, max.	70 °C	O-Ring	Silicone
Sealing	Silicone	Torque for connecting adapter, min.	4 Nm
Torque for connecting adapter, max.	4 Nm	Torque for lock nut, min.	3.8 Nm
Torque for lock nut, max.	4 Nm	Explosion protection type	Improved safety Ex e
Standards	IEC 60079-0, EN 60079-0, IEC 60079-7, EN 60079-7, EN 60079-31, IEC 60079-31	Installation guidelines	See assembly instructions

**Classifications**

ETIM 6.0	EC000451	ETIM 7.0	EC000451
eClass 9.0	27-14-44-25	eClass 9.1	27-14-44-35
eClass 10.0	27-14-44-25		

**Approvals**

ROHS	Conform
------	---------

**Downloads**

Brochure/Catalogue	<a href="#">CAT 5 ENCL 17/18 EN</a>
Engineering Data	<a href="#">EPLAN</a>
Engineering Data	<a href="#">STEP</a>