

## Upper part of housing - ICS25-TL100X12-7035 - 2203883

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Component housing, width: 25 mm ,With transparent hinged cover, , Upper part



### Your advantages

- Flexible use, thanks to the modular system and unique modularity in the connection technology
- Standardized connections such as RJ45, USB, D-SUB, and antenna sockets as integrative components
- Optimal space utilization, as well as adaptability of design, colors, and printing
- 8-pos. DIN rail connectors for easy module-to-module communication

### Key Commercial Data

Packing unit	10 pc
Minimum order quantity	10 pc
GTIN	
GTIN	4055626465586
Weight per Piece (excluding packing)	12.400 g
Custom tariff number	85389099
Country of origin	Germany

### Technical data

#### Item properties

Brief article description	Upper part of housing
Type	ICS25-TL100X12-7035
Order No.	2203883
Housing type	Component housing
Type	Upper part

#### Dimensions

Width [ w ]	25 mm
Height [ h ]	100 mm

# Upper part of housing - ICS25-TL100X12-7035 - 2203883

## Technical data

### Dimensions

Depth [ d ]	14.35 mm
-------------	----------

### Material data

Color (RAL)	light gray (7035)
Flammability rating according to UL 94	V0
Housing material	PA 6.6

### Ambient conditions

Ambient temperature (storage/transport)	-40 °C ... 70 °C
Ambient temperature (assembly)	-5 °C ... 100 °C
Ambient temperature (operation)	-40 °C ... 100 °C (observe derating)

### Mechanical strength/tumbling barrel

Height of fall	50 cm
Number of drop cycles	50

### Thermostability (Ball Thrust Test)

Specification	IEC 60695-10-2:2014-02
Temperature	125 °C
Test duration	1 h
Force	20

### Test for assessing the risk of fire (glow wire)

Specification	IEC 60695-2-11:2014-02
Temperature	850 °C
Time of exposure	30 s

### Test for substances that would hinder coating with paint or varnish

Specification	VW PV 3.10.7:2005-02
---------------	----------------------

### General information

Type of note	Assembly instruction:
Note	Refer to the data sheet for the range in the download area.

### Packaging information

Pieces per package	10
Denomination packing units	Pcs.

### Standards and regulations

Flammability rating according to UL 94	V0
--	----

### Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

# Upper part of housing - ICS25-TL100X12-7035 - 2203883

## Classifications

### eCl@ss

eCl@ss 5.1	27180505
eCl@ss 6.0	27180800
eCl@ss 7.0	27182702
eCl@ss 8.0	27182702
eCl@ss 9.0	27182702

### ETIM

ETIM 5.0	EC001031
ETIM 6.0	EC001031

## Approvals

### Approvals

---


#### Approvals

UL Recognized

---

#### Ex Approvals

### Approval details

UL Recognized		<a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a>	FILE E 240868
---------------	---	---	---------------

## Accessories

### Accessories

#### Component housing lower part

#### Mounting base housing - ICS25-B100X98-V-7035 - 2203881



DIN rail housing, Lower part, Level 1: with vents, width: 25 mm, Cross connection: without bus connector, color: light gray (7035)

## Upper part of housing - ICS25-TL100X12-7035 - 2203883

### Accessories

Mounting base housing - ICS25-B100X120-V-7035 - 2203884



DIN rail housing, Lower part, Level 1: with vents, width: 25 mm, Cross connection: without bus connector, color: light gray (7035)

---

### Connection plate

Connection plate - ICS25-F22S-7035 - 2203890



ICS-Filler, closed, color: light gray, width: 25 mm

---

Connection plate - ICS25-F45S-7035 - 2203891



ICS-Filler, closed, color: light gray, width: 25 mm

---

Connection plate - ICS25-F22V-7035 C-SAMPLE - 1079495



Component housing, Filler, with vents, color: light gray, width: 25 mm

---

Connection plate - ICS25-F45V-7035 - 1079492

Component housing, Filler, with vents, color: light gray, width: 25 mm

---

Connection plate - ICS25-F22J-7035 - 2203895



ICS-Filler, with RJ45 function cutout, color: light gray, width: 25 mm

## Upper part of housing - ICS25-TL100X12-7035 - 2203883

### Accessories

---

Connection plate - ICS25-F22U-7035 - 1053046



ICS-Filler, with USB function cutout, color: light gray, width: 25 mm

---

Connection plate - ICS25-F22A-7035 - 2203894



ICS-Filler, with antenna function cutout, color: light gray, width: 25 mm

---

Connection plate - ICS25-F45D15-7035 - 2203896



ICS-Filler, With D-SUB 15 function cutout, color: light gray, width: 25 mm

---

### DIN rail connector

DIN rail bus connectors - TBUS8-25,0-PPPPPPPP-7035 - 2202891



DIN rail connector, number of positions: 8, pitch: 2.54 mm, color: light gray, 8 parallel contacts

---

DIN rail bus connectors - TBUS8-25,0-PPPPPPPS-7035 - 2202890



DIN rail connector, number of positions: 8, pitch: 2.54 mm, color: light gray, 7 parallel contacts/1 series contact

---

## Upper part of housing - ICS25-TL100X12-7035 - 2203883

### Accessories

DIN rail bus connectors - TBUS8-25,0-PPPPPPSS-7035 - 2202895



DIN rail connector, number of positions: 8, pitch: 2.54 mm, color: light gray, 6 parallel contacts/2 series contacts

---

### PCB headers

Feed-through header - ICC25-H/4L5,0-7035 - 2203902



PCB headers, number of positions: 4, pitch: 5 mm, color: light gray, Product with pin output on left side

---

Feed-through header - ICC25-H/4R5,0-7035 - 2203903



PCB headers, number of positions: 4, pitch: 5 mm, color: light gray, Product with pin output on right side

---

### PCB plug

Printed-circuit board connector - PSPT 2,5/ 4-ST KMGY - 2202344



PCB connector, number of positions: 4, pitch: 5 mm, color: light gray

---

Printed-circuit board connector - MSTBT 2,5 HC/ 4-STP GY7035 - 2200332



PCB connector, number of positions: 4, pitch: 5 mm, color: light gray

---