

TE Internal #: 2267072-1

Push Button Switches, Single Pole - Single Throw Configuration (Pole-Throw), Switch, Single Actuator, Extended Actuator Profile, Unthreaded, Off [On]

View on TE.com >



Relays, Contactors & Switches > Switches > Push Button Switches



Configuration (Pole-Throw): Single Pole - Single Throw

Push Button Switch Product Type: Switch

Number of Actuators: Single
Actuator Profile: Extended
Bushing Style: Unthreaded

Features

Product Type Features

Dust Proof	No
Push Button Switch Product Type	Switch
Illuminated	No
Actuator Style	Round

Configuration Features

ESD Grounding Terminal	Without
Ganged	No
Configuration (Pole-Throw)	Single Pole - Single Throw
Number of Actuators	Single
Snap Action	Without
Support Bracket	Without
Tactile	No
Operating Function	Off [On]

Electrical Characteristics

Push Button Switch Voltage Rating	20 VDC	
-----------------------------------	--------	--

Body Features

Case Material	Diallyl Phthalate (DAP)
Actuator Material	Thermoplastic Polyester
Actuator Profile	Extended



Bushing Style	Unthreaded
Actuator Color	Black
Contact Features	
Push Button Switch Contact Current Rating	.4 A
Switch Contact Plating Material	Gold
Termination Features	
Termination Type	Printed Circuit
Mechanical Attachment	
Mounting Angle	Vertical
Push Button Switch Mounting Type	Through Hole
Housing Features	
Low Profile	No
Process Sealed	No
Dimensions	
Actuator Length	3.94 mm[.155 in]
Usage Conditions	
Temperature Rating	Standard
Packaging Features	
Packaging Method	Loose Piece
Other	

Product Compliance

Comment

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2022 (223) Candidate List Declared Against: JUL 2021 (219) SVHC > Threshold: Pb (3.7% in component part) Article Safe Usage Statements:

(On) indicates momentary position.



Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.

Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC
	Free

Solder Process Capability

Wave solder capable to 260°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts











Customers Also Bought























Documents

Product Drawings

PMS9P1B10M2RE

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2267072-1_A_c-2267072-1-a.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2267072-1_A_c-2267072-1-a.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2267072-1_A_c-2267072-1-a.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

Push Button Switches, Single Pole - Single Throw Configuration (Pole-Throw), Switch, Single Actuator, Extended Actuator Profile, Unthreaded, Off [On]



Subminiature Switches

English