

TE Internal #: 2267078-2

Toggle Switches, Single Pole - Double Throw Configuration (Pole-Throw), Sealed, Gold, Gold, Terminal Seal (Epoxy), Baton Short, On

On, .4 A, 20 V

View on TE.com >



Relays, Contactors & Switches > Switches > Toggle Switches



Configuration (Pole-Throw): Single Pole - Double Throw

Sealed Toggle Switch: **Yes**Contact Base Material: **Gold**

Switch Contact Plating Material: Gold

Process Sealed: No

Features

Product Type Features

Product Type Sw	witch
Sealed Toggle Switch	es
Toggle Style Ba	Saton Short
Toggle Switch Type	oggle
Toggle Actuation Ve	'ertical

Configuration Features

Configuration (Pole-Throw)	Single Pole - Double Throw
Operating Function	On On

Electrical Characteristics

Toggle Switch Voltage Rating	20 VAC

Body Features

Color	Red
Toggle Switch Seal Type	Terminal Seal (Epoxy)
Bushing Style	Plain, Unthreaded

Contact Features

Contact Base Material	Gold
Switch Contact Plating Material	Gold
Toggle Switch Contact Current Rating	.4 A



Termination Features

Termination Type	Printed Circuit
Mechanical Attachment	
Toggle Switch Mounting Type	Through Hole
Housing Features	
Process Sealed	No
Dimensions	
Toggle Length	5.59 mm[.22 in]
Industry Standards	
UL Rating	Flame Rating Only
UL Flammability Rating	UL 94V-0

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2022 (223) Candidate List Declared Against: JUL 2021 (219) SVHC > Threshold: Pb (3.7% in component part) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Wave solder capable to 260°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on



requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts











Customers Also Bought















TE Part #YDJT14E09-35PNV001
RECP ASSY



TE Part #1825223-3

TE Part #66441-17-6P
PLUG ASSY

Documents

Product Drawings

TMS1T5B2M2RE

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2267078-2_A_c-2267078-2-a.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2267078-2_A_c-2267078-2-a.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2267078-2_A_c-2267078-2-a.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

Subminiature Switches

English