

Parts and applications overview:



Material	Surface	DIN	Shape	Left hand cutting / right hand cutting	Thread	Tenacity classes	Nominal thread size	Article no.	Page
HSS		DIN 352			M	800 N/mm²	M 2 - M 52	230 020 - 230 520	158
HSS		DIN 352			M	800 N/mm²	M 3 - M 20	230 030 Li - 230 200 Li	158
HSSE Co 5		DIN 352			M	1000 N/mm²	M 2 - M 24	230 020 E - 230 240 E	158
HSS		DIN 2181			MF	800 N/mm²	MF 3 - MF 52	235 030 - 235 520	160
HSS		DIN 5157			G (BSP)	800 N/mm²	G 1/8 - G 2"	236 018 - 236 020	162
HSS		DIN 352			Ww (BSW)	800 N/mm²	1/16 - 2"	246 116 - 246 020	163
HSS		DIN 352			UNC	800 N/mm²	Nr. 2 - 2"	246 020 UNC - 246 200 UNC	164
HSS		DIN 352			UNF	800 N/mm²	Nr. 2 - 1 1/2"	246 020 UNF - 246 112 UNF	165
HSS		DIN 382	C		NPT	800 N/mm²	1/16 - 2"	231 116 NPT - 231 020 NPT	169
HSS		DIN 352	B		M	800 N/mm²	M 3 - M 12	231 030 - 231 120	168
HSSE Co 5		DIN 352	B		M	1000 N/mm²	M 3 - M 12	231 030 E - 231 120 E	168
HSS		DIN 5157	B		G (BSP)	800 N/mm²	G 1/8 - G 1"	236 210 - 236 238	170



HSS		DIN 22568	B		M	800 N/mm²	M 2 - M 52	237 020 - 237 520	159
HSS		DIN 22568	B		M	800 N/mm²	M 3 - M 12	238 030 - 238 120	159
HSS		DIN 22568	B		M	800 N/mm²	M 3 - M 20	237 030 Li - 230 200 Li	159
HSSE Co 5		DIN 22568	B		M	1000 N/mm²	M 2 - M 24	237 020 E - 237 240 E	159
HSS		DIN 22568	B		MF	800 N/mm²	MF 3 - MF 52	239 030 - 239 520	161
HSS		DIN 24231	B		G (BSP)	800 N/mm²	G 1/8 - G 2"	240 018 - 240 020	162
HSS		DIN 22568	B		Ww (BSW)	800 N/mm²	1/16 - 2"	247 116 - 247 020	163
HSS		DIN 22568	B		UNC	800 N/mm²	Nr. 2 - 2"	240 020 UNC - 240 112 UNC	164
HSS		DIN 22568	B		UNF	800 N/mm²	Nr. 2 - 1 1/2"	240 020 UNF - 240 112 UNF	165
HSS		DIN 382			M	800 N/mm²	M 3 - M 30	267 030 - 267 300	169
HSS		DIN 382	B		G (BSP)	800 N/mm²	G 1/8 - G 1"	267 610 - 267 638	170