


Item no.: 237-102  
 Product description: Modular terminal block with wire protection 2-pole Pin spacing 5 mm / 0.197 in



Produkt kann von Bild abweichen / product may differ

Packing unit 600 6\*100 pieces

RoHS compliant

|                                  |                           |
|----------------------------------|---------------------------|
| Product group                    | 4 (Printed Circuit)       |
| Pin spacing from                 | 5 mm                      |
| Pin spacing from                 | 0.197 in                  |
| pole count                       | 2                         |
| Cross section [mm <sup>2</sup> ] | 0.5 - 2.5 mm <sup>2</sup> |
| Cross section [AWG]              | 20 - 14 AWG               |
| Connection method                | SCREW CONNECTION          |
| Measured voltage EN              | 250 V                     |
| Measured shock voltage           | 2.5 kV                    |
| Pollution degree                 | 2                         |
| Current intensity EN             | 16 A                      |
| Weight                           | 1.98 g                    |
| Color                            | grey                      |
| Wiring type                      | Side-entry                |
| No. of connection Points         | 2                         |
| No. of potentials                | 2                         |
| Height                           | 11 mm                     |
| Height                           | 0.433 in                  |
| Width                            | 5 mm                      |

|       |          |
|-------|----------|
| Width | 0.197 in |
| Depth | 9 mm     |
| Depth | 0.354 in |



|                   |         |
|-------------------|---------|
| Strip length from | 5 mm    |
| Strip length to   | 7 mm    |
| Strip length      | 0.24 in |



| Item number | Admission office    | Approval no. | Voltage [V] | Current [A] | Cross section [ mm <sup>2</sup> ] |
|-------------|---------------------|--------------|-------------|-------------|-----------------------------------|
| 237-102     | CBcertificateINDIEN | 98-02629     | 250         | 16          | 0,5-2,5                           |
| 237-102     | CCA                 | NL6290       | 250         | 24          | 0,5-2,5                           |
| 237-102     | CSA                 | 18677-6      | 300         | 10          | 20-14                             |
| 237-102     | KEMA                | 110204.13    | 250         | 24          | 0,5-2,5                           |
| 237-102     | RMR                 | 11130002     | 250         | 16          | 0,5-2,5                           |
| 237-102     | UR                  | E45172       | 300         | 10          | 18-14                             |

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected