


Item no.: 237-103  
 Product description: Modular terminal block with wire protection 3-pole Pin spacing 5 mm / 0.197 in



Produkt kann von Bild abweichen / product may differ

Packing unit 400 4\*100 pieces

RoHS compliant

Product group	4 (Printed Circuit)
Pin spacing from	5 mm
Pin spacing from	0.197 in
pole count	3
Cross section [mm <sup>2</sup> ]	0.5 - 2.5 mm <sup>2</sup>
Cross section [AWG]	20 - 14 AWG
Connection method	SCREW CONNECTION
Measured voltage EN	250 V
Measured shock voltage	2.5 kV
Pollution degree	2
Current intensity EN	16 A
Weight	2.975 g
Color	grey
Wiring type	Side-entry
No. of connection Points	3
No. of potentials	3
Height	11 mm
Height	0.433 in
Width	5 mm

Width	0.197 in
Depth	9 mm
Depth	0.354 in



Strip length from	5 mm
Strip length to	7 mm
Strip length	0.24 in



Item number	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [ mm <sup>2</sup> ]
237-103	CBcertificateINDIEN	98-02629	250	16	0,5-2,5
237-103	CCA	NL6290	250	24	0,5-2,5
237-103	CSA	18677-6	300	10	20-14
237-103	KEMA	110204.13	250	24	0,5-2,5
237-103	RMR	11130002	250	16	0,5-2,5
237-103	UR	E45172	300	10	18-14

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected