

**VG EMV GEN 4 (EMC cable gland with clamping cage)  
VG M40 EMV-4 MS 22-32**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

**Similar to illustration**

**Produktabbildung**

Brass cable gland for shielding against interference frequencies with a screening attenuation of up to 100 dB. Contact with cable shield by means of spring washer.

**General ordering data**

Type	VG M40 EMV-4 MS 22-32
Order No.	<a href="#">2435190000</a>
Version	VG EMV GEN 4 (EMC cable gland with clamping cage), Cable glands, M 40, 9, OD min. 22 - OD max. 32 mm, IP54, IP66, IP67, IP68 - 5 bar (30 min.), IP69K, Brass, nickel-plated
GTIN (EAN)	4050118446944
Qty.	5 pc(s).

**VG EMV GEN 4 (EMC cable gland with clamping cage)  
VG M40 EMV-4 MS 22-32**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

**Technical data**
**Dimensions and weights**

Length	69.5 mm	Length (inches)	2.736 inch
Net weight	0.278 g		

**Environmental Product Compliance**

REACH SVHC	Lead 7439-92-1
------------	----------------

**General information**

Material	Brass, nickel-plated	Cable glands	metric
External thread	M 40	Pitch of thread	1.5 mm
Length of thread	9 mm	AF size 1	50 mm
AF size 2	50 mm	Protection degree	IP66, IP68 - 5 bar (30 min.), IP69K
Protection degree with GWDR	IP54, IP66, IP67, IP68 - 5 bar (30 min.), IP69K	Operating temperature range, min.	-40 °C
Operating temperature range, max.	100 °C	Outer cable diameter, min.	22 mm
Outer cable diameter, max.	32 mm	Shield diameter, min.	18 mm
Shield diameter, max.	27 mm	Clamp insert	Polyamide
O-Ring	NBR	Seal insert	CR
Tightening torque	12 Nm		

**Classifications**

ETIM 6.0	EC000441	ETIM 7.0	EC000441
eClass 9.0	27-14-44-32	eClass 9.1	27-14-44-32
eClass 10.0	27-14-44-32		

**Approvals**

ROHS	Conform
------	---------

**Downloads**

Brochure/Catalogue	<a href="#">CAT 3 HDC 17/18 EN</a> <a href="#">CAT 5 ENCL 17/18 EN</a>
Engineering Data	<a href="#">EPLAN</a>
Engineering Data	<a href="#">STEP</a>