

**Torque screwdriver set TorqueVario®-S
assorted variably adjustable, 13-pcs. in box
(26893) 0,8- 5,0 Nm**



Wiha Werkzeuge GmbH
Obertalstraße 3-7
78136 Schonach

E-Mail: info.de@wiha.com
Tel.: +49 (0)7722 959-0



Article No.: 26893

GTIN: 4010995268930

Unit: Set

Meets your requirements: A variably settable torque covers a large application area.

Simplifies your work: All tools securely arranged in a robust and clearly laid out box.

Lowers your costs: The correct torque protects you from warranty claims.

Protects your health: With the patented SoftFinish® handle design, ensuring work is kind to hands and muscles. Recommended by doctors and therapists at German Campaign for Healthier Backs.

Increases your efficiency: The correct torque avoids damaging material and no follow-up work is necessary.

The TorqueVario®-S torque screwdriver set provides the right torque for process safety. The tool set contains an ergonomically shaped torque screwdriver with an integrated numeric scale, 10 standard bits for all applications, a bit holder and an adjusting tool. All components are arranged practically in a high-grade, sturdy box, where they are easy to identify. The torque screwdriver covers a wide variety of applications with a torque range between 0.8 and 5.0 Nm. A clearly audible, physically perceptible signal emitted when the torque is produced guarantees process safe torque mechanics, protecting against damage to materials and eliminating the need for retouching. With a release accuracy of +/- 6%, the torque tool complies with EN ISO 6789 requirements.

Standards: DIN EN ISO 6789.

Application: Suitable for controlled fastening of predefined torques for tasks such as industrial assembly work or fastening of cutting inserts.

Lieferumfang	<p>1 x Adjusting tool for torque screwdriver with long handle (26864) 146 mm</p> <p>1 x Bit holder clamping with ball for torque screwdriver with long handle (27526) 1/4 mm, 162 mm</p> <p>1 x Bit Standard 25 mm Hexagon 1/4" (01705) 3,0</p> <p>1 x Bit Standard 25 mm Hexagon 1/4" (01706) 4,0</p> <p>1 x Bit Standard 25 mm Phillips 1/4" (01657) PH1</p> <p>1 x Bit Standard 25 mm Phillips 1/4" (01658) PH2</p> <p>1 x Bit Standard 25 mm Pozidriv 1/4" (01688) PZ1</p> <p>1 x Bit Standard 25 mm Pozidriv 1/4" (01689) PZ2</p> <p>1 x Bit Standard 25 mm TORX® 1/4" (01716) T10</p> <p>1 x Bit Standard 25 mm TORX® 1/4" (01717) T15</p> <p>1 x Bit Standard 25 mm TORX® 1/4" (01718) T20</p> <p>1 x Bit Standard 25 mm TORX® 1/4" (01719) T25</p> <p>1 x Torque screwdriver TorqueVario®-S Variable torque limit settings (26463) 0,8-5,0 Nm, 4 mm</p>
--------------	---

Nm	0,8- 5,0 Nm
----	-------------

Weight	779 g
--------	-------

Serie	2852 S10
-------	----------

Anwendungsszenarien	Suitable for controlled fastening of predefined torques for tasks such as industrial assembly work or fastening of cutting inserts.
---------------------	---

Customs tariff number	82054000
-----------------------	----------

Product group	26893
---------------	-------