

<b>Description</b>	Three phase set; with 35 mm <sup>2</sup> high-current tbs	
<b>Remarks</b>		
<b>Item properties</b>		
	<b>Miscellaneous</b>	
	<b>Name</b>	<b>Value</b> <span style="float: right;"><b>Unit</b></span>
	Total number of connection points	10
	Total number of potentials	5
	Ratings per	IEC/EN 60947-7-1
	Rated voltage (III / 3) [V]	1000 <span style="float: right;">V</span>
	Rated impulse voltage (III / 3) [kV]	8 <span style="float: right;">kV</span>
	Pollution degree (1)	3
	Number of levels	1
	Connection technology	POWER CAGE CLAMP
	Number of connection points connector	10
	Actuation type	Operating tool
	Connectable conductor materials	Copper
	Solid conductor	6 ... 35 mm <sup>2</sup> / 10 ... 2 AWG
	Fine-stranded conductor	6 ... 35 mm <sup>2</sup> / 10 ... 2 AWG
	Strip length	25 mm / 0.98 Inch
	Type of wiring	Side-entry wiring
	Design	horizontal
	Marking level	Side marking
	Insulating material	Polyamide 66 (PA 66)
	Fire load [MJ]	6.193 <span style="float: right;">MJ</span>
	Weight [g]	425.675 <span style="float: right;">g</span>
	Height from upper-edge of DIN-35 rail	63 mm / 2.48 Inch
	Depth	86 mm / 3.386 Inch
	Type of mounting	DIN-35 x 15 carrier rail
	Safety information 1	sively on DIN-35 x 15 rail; 2.3 mm thick