

Description	Three phase set; with 50 mm ² high-current tbs
Remarks	

Item properties

Miscellaneous		
Name	Value	Unit
Total number of connection points	10	
Total number of potentials	5	
Ratings per	IEC/EN 60947-7-1	
Rated voltage (III / 3) [V]	1000	V
Rated impulse voltage (III / 3) [kV]	8	kV
Pollution degree (1)	3	
Number of levels	1	
Connection technology	POWER CAGE CLAMP	
Number of connection points connector	10	
Actuation type	Operating tool	
Connectable conductor materials	Copper	
Solid conductor	10 ... 50 mm ² / 8 ... 1/0 AWG	
Fine-stranded conductor	10 ... 70 mm ² / 8 ... 2/0 AWG	
Strip length	30 mm / 1.18 Inch	
Type of wiring	Side-entry wiring	
Design	horizontal	
Marking level	Side marking	
Insulating material	Polyamide 66 (PA 66)	
Fire load [MJ]	10.658	MJ
Weight [g]	812.38	g
Height from upper-edge of DIN-35 rail	87 mm / 3.425 Inch	
Depth	94 mm / 3.701 Inch	
Type of mounting	DIN-35 x 15 carrier rail	
Safety information 1	sively on DIN-35 x 15 rail; 2.3 mm thick, copper	