

Description	Three phase set; with 95 mm ² high-current tbs		
Remarks			
Item properties	Miscellaneous		
	Name	Value	Unit
	Total number of connection points	10	
	Total number of potentials	5	
	Ratings per	IEC/EN 60947-7-1	
	Rated voltage (III / 3) [V]	1000	V
	Rated impulse voltage (III / 3) [kV]	8	kV
	Pollution degree (1)	3	
	Number of levels	1	
	Connection technology	POWER CAGE CLAMP	
	Number of connection points connector	10	
	Actuation type	Operating tool	
	Connectable conductor materials	Copper	
	Solid conductor	25 ... 95 mm ² / 4 ... 4/0 AWG	
	Fine-stranded conductor	25 ... 95 mm ² / 4 ... 4/0 AWG	
	Strip length	35 mm / 1.38 Inch	
	Type of wiring	Side-entry wiring	
	Design	horizontal	
	Marking level	Side marking	
	Insulating material	Polyamide 66 (PA 66)	
	Weight [g]	1340.75	g
	Height from upper-edge of DIN-35 rail	101 mm / 3.976 Inch	
	Depth	107 mm / 4.213 Inch	
Type of mounting	DIN-35 x 15 carrier rail		
Safety information 1	sively on DIN-35 x 15 rail; 2.3 mm thick, copper		